



kramer

TBUS-6xl

Interfaccia per Connessioni da Tavolo



The TBUS-6xl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately

FEATURES

Inner Frame - 3 different "T6F" inner frame options are available

Power Sockets - 8 different "TS" single power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket

Optional Accessories - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available

WEIGHT: - TBUS-6: 1.35 kg Table clamps: 0.25 kg

OPERATING TEMPERATURE RANGE: - 5° a 45°C

Installation Requirement - Table cutout of 225mm x 123mm (8.87" x 4.85")

OPERATING HUMIDITY RANGE: - 10 a 90% RHL, no-condensa

Weight - 1.35 kg (2.8 lbs) approx.; table clamps: 0.25 kg (0.6 lbs) approx



kramer

TECHNICAL SPECIFICATIONS

FUSE RATING: T 6.3A 250V

OPTIONS: Insert kit

Product Dimensions 24.30cm x 0.00cm x 14.00cm (9.57" x 0.00" x 5.51") W, D, H

Product Weight 1.7kg (3.8lbs) approx

Shipping Dimensions 36.00cm x 26.50cm x 21.00cm (14.17" x 10.43" x 8.27") W, D, H

Shipping Weight 2.6kg (5.7lbs) approx



kramer

CONFIGURATIONS

TBUS-6xl(B)	Enclosure - Black Sand Blasted Anodized Aluminum Top
TBUS-6xl(BC)	Enclosure - Silver Sand Blasted Anodized Aluminum Top

