

# ADC-VS123

## SPECIFICATIONS

### RECORDING CHANNELS

H.264 & MJPEG

### SUPPORTED PROTOCOLS

HD/SD Analog, HD/SD TVI, HD/SD CVI

### SUPPORTED RESOLUTIONS

1080p, 720p, D1 (704p x 480p)

### ETHERNET CONNECTION

10/100Base-T (RJ45) LAN

### CHIPSET FAMILY

S2L

### LED INDICATORS

3

### TOGGLE SWITCH

HD/SD

### DIMENSIONS

5.51 x 3.54 x 1.18" (140 x 90 x 30 mm)

### OPERATING TEMPERATURE

32°F to 104°F (0°C - 40°C)

### OPERATING HUMIDITY

0% to 80%

## REQUIREMENTS

### POWER

12 VAC Adapter or PoE

### NETWORK

Ethernet connection to broadband Internet



## HD Video Server

With support for HD video, the ADC-VS123 makes it easy to add any analog camera to the Alarm.com ecosystem. Simply connect the VS123 to power, the existing video camera's coaxial cable, and a router to enjoy the benefits of a connected video solution. View live and recorded video remotely and add to a Stream Video Recorder for continuous local recording. The VS123 integrates with Alarm.com, providing easy post-installation troubleshooting and enhanced security.




### FEATURES

- Supports HD and SD analog cameras
- 1-channel analog video input and 1-channel analog video output
- Works with the Alarm.com Customer Website and Mobile App
- Remote management and troubleshooting

### INCLUDED ACCESSORIES

- Power adapter
- Mounting hardware
- Termination resistor/dust-proof cap

### LED GUIDE

	LED STATUS	DESCRIPTION
NETWORK 	Off	No local or Internet connection
	Solid Green	Connected to Alarm.com
	Blinking Green	Data transfer with Alarm.com
ACTIVE 	Off	The camera is not being streamed
	Blinking Green	The camera is being streamed
POWER 	Off	Active intranet connection
	Solid Green	Device is powered