

## SPECIFICATIONS AND MECHANICAL DIMENSIONS

- LE Product Number: LE-875
- Mounting: Wall or Pole Mounted [With optional mounting kit
- Installations: Outdoor - Weather Resistant

## COMPATIBILITY

- ONVIF Profile "S" & "T"



## SPECIFICATIONS (Speaker)

- Pick Up Pattern: Omni-directional, within 15' diameter circle
- Type: Electret condenser
- Sensitivity: -45 dBV/Pa 1 Pa = 94 dB SPL
- Frequency Response: 40 Hz to 15 kHz
- Output: RTSP stream {Line level 0 dBV, 600Ω @ 1 kHz} Current Drain: 1 A
- Power: Power over Ethernet IEEE802.3af optional external 5V DC 2A

## NETWORK AUDIO

- Audio Streaming: One-Way (half and full duplex)
- Audio Compression: G.711 mu-Law
- Supported Protocols: ONVIF Profile T, IPv4, HTTPS, RTSP, RTP, TCP
- Application Prog Interface: Open API for software integration
- Audio Analysis and Classification: Decibel level threshold, Explosions, Aggression, Car Alarm, Broken Glass
- Event Triggers: Audio analytics, audio level
- Event Actions: HTTP Post, TCP notification, WAV file playback, external output activation, pre and post-alarm audio recording

## HOUSING

- Material: Aluminum Alloy NEMA Rated Enclosure
- Weight: 2.0 lbs
- Dimensions: 4.2" W x 6.5" H x 3" D