

# 5G108-BL5

GigaMax Cat 5e QuickPort Jack QuickPack, 25-pack, Blue



**UPC Code :** 078477203040  
**Country Of Origin :** United States  
**RoHS Compliant :** Yes

## Technical Information

### Product Features

**Body Color :** Blue  
**Brand :** GigaMax  
**Cable Type :** 8-Conductor UTP Copper Cat 5, 5e and 6  
**Category Rating :** Cat 5e  
**Color :** Blue  
**Connector Feature :** Channel-Rated  
**Contact Base Material :** Phosphor Bronze  
**Contact Sub-Surface Material :** 100 microinches thick Nickel-Plated  
**Contact Surface Material :** 50 microinches thick Gold-Plated  
**Flammability :** Rated V-0 per UL 94  
**Module Style :** Connector  
**Module Type :** Category 5e  
**Ordering Notes :** Bulk Package of 25  
**Packaging :** QuickPack 25/bag  
**Position / Conductor :** 8P8C  
**Shielding :** UTP  
**Standards and Certifications :** TIA/EIA cULus Listed  
**Termination Type :** 110 Punchdown  
**Warranty :** 1 Year Limited

### Material Specifications

**Body Color :** Blue  
**Body Material :** High-Impact Fire-Retardant Plastic  
**Contact Base Material :** Phosphor Bronze  
**Contact Sub-Surface Material :** 100 microinches thick Nickel-Plated  
**Contact Surface Material :** 50 microinches thick Gold-Plated

### Mechanical Specifications

**Cable Type :** 8-Conductor UTP Copper Cat 5, 5e and 6  
**Connector Feature :** Channel-Rated  
**Position / Conductor :** 8P8C  
**Product ID :** Permanently laser-engraved  
**Style Name :** GigaMax  
**Termination Type :** 110 Punchdown  
**Wiring Standard :** T568A T568B

### Performance Specifications

**Module Type :** Category 5e

### Standards and Certifications

**ACA :** Compliant  
**CSA :** Certified  
**FCC :** Part 68 Compliant  
**NEC :** Article 800 Compliant  
**TIA/EIA :** TIA-568-B  
**UL :** cULus Listed

## Features and Benefits

- Available in 13 colors
- Dual wiring code label allows connector to be wired to either T568A or T568B
- Individual port configurability allows specification flexibility
- Robust one-piece lead-frame design increases power-carrying capacity and efficiency, while providing improved durability
- Narrow connector allows high port density in a small area
- Will exceed IEEE 802.3bt standard up to 0.7 amps (140 watts) continuously
- Supports high-megabit and shared-sheath applications
- Available individually, in bulk packages of 25, and in bulk packages of 150 with a JackRapid™ Punchdown Tool

- IEEE 802.3bt PoE Type 1 (15.4 Watts) formerly 802.3af, Type 2 (30 Watts) formerly 802.3at, Type 3 (60 Watts), Type 4 (90 Watts)
- Cisco UPoE (60 Watts), UPoE+ (90 Watts)
- Power over HDBaseT™ PoH (95 Watts)
- UL 2043 Plenum Certified

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

