

NMP01250 AirCell® 50 Ohm Connectors

For use with AirCell® 1/2" 50 Ohm Plenum, Conduit and In-Conduit Cables

Description	NMP01250
General Specifications	
Interface	N Male
Body Style	Straight
Electrical Specifications	
Impedance, Ohms	50
Operating Frequency Band	0.3 MHz to 6 GHz
Dielectric Withstand Voltage	2 kV DC
3rd Order IMD	-140 dBc minimum, -150 typical
3rd Order IMD, Test Method	2 x 20 Watt carriers
Average Power	0.6 kW
Peak Power, maximum	10 kW
Insertion Loss, typical	0.05
Shielding Effectiveness	-130 dB
Return Loss (VSWR)	
DC to 1 GHz	30 dB (1.06)
1 GHz to 2 GHz	31 dB (1.06)
2 GHz to 3 GHz	32 dB (1.06)
3 GHz to 4 GHz	25 dB (1.12)
4 GHz to 5 GHz	20 dB (1.22)
5 GHz to 6 GHz	15 dB (1.43)
Mechanical Specifications	
Outer Contact Plating	Silver
Inner Contact Plating	Silver
Interface Durability	500 cycles
Interface Durability Test Method	IEC 16916
Minimum Connector Pull-off Force	200 lbs
Environmental Specifications	
Operating Temperature, °F (°C)	-40° to 158° (-40° to 70°)
Storage Temperature, °F (°C)	-40° to 158° (-40° to 70°)
Installation Temperature, °F (°C)	23° to 122° (-5° to 50°)
Immersion Test Method	IEC60529:2001 IP68
Corrosion Test Method	MIL-STD-1344A
Thermal Shock Test Method	MIL-STD-202F
Vibration Test Method	MIL-STD-202F
Regulatory Compliance/Certifications	
RoHS 2011/65/EU Compliant	
TL 9000 H-V - All Cables designed and manufactured under this quality management system	



©2016 Trilogly Communications, Inc. All rights reserved. All trademarks identified by ® are registered trademarks of Trilogly Communications. All Specifications are subject to change without notice. See www.triloglycoax.com or call 800-TRILOGY for the most current information. Revised 09/15/16

Notice: Trilogly disclaims any liability or responsibility for the results of improper or unsafe installation, inspection, maintenance or removal practices