



nexTouch[™]
Sectional Mortise Keypad Lock



An ASSA ABLOY Group brand

ASSA ABLOY



TECHNICAL SPECIFICATIONS

Door Specifications: Fits into the standard mortise door prep

Backset: 2-3/4" (70mm) standard backset

Door Thickness: 1-3/4" (44mm) door thickness standard; please specify for other door thicknesses

Handing: Field reversible

Latchbolt: 3/4" spring latchbolt standard, 1" throw deadlocking latchbolt optional

Strike: Curved lip strike with 1-1/4" (32 mm) lip length standard

Cylinder: Accepts conventional, interchangeable core, security and high security cylinders, and other manufacturers' keyway cylinders

ANSI/BHMA: Certified ANSI/BHMA Grade 1

UL/cUL: Functions are UL - cUL Fire Listed for use on fire doors having a rating up to and including 3-hours

Warranty: 1-year electrical warranty; 3-year mechanical and finish warranty

Environmental Specifications: Operating temperature: -40°F to +140°F (-40°C to +60°C) at 95% relative humidity when used with an external power supply

Power Source: 4 AA alkaline batteries (included) with optional hardwire input for 9VDC external power; 9V battery power backup on keypad

Interface: Capacitive touchscreen or pushbutton keypad

User Codes: Up to 500 unique user codes



FINISHES

ANSI/BHMA Code	Finish Description
605 (US3)	Bright Brass, Clear Coated
613E (US10BE)	Dark Oxidized Satin Bronze - equivalent
626 (US26D)	Satin Chrome Plated
BSP	Black Suede Powder Coat

LEVERS

ARCADIA ARR



AUGUSTA AUR



CARMEL CRR



JEFFERSON JNR



MONROE MOR



PACIFIC BEACH PBR



PINEHURST PNR



VIRGINIA VNR



Yale Locks & Hardware is a division of Yale Security, Inc., an ASSA ABLOY Group Company. Copyright © 2018, Yale Security, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Yale Security, Inc. is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.

YALE, with its unique global reach and range of products, is the world's favorite lock.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

42984 - 3/18N