

# CHeKT 30W IP Horn Outdoor Speaker

Available Model:  
**CKIPS30W**



## 30 Watt IP Speaker

Combine video & audio systems into a single proactive security solution.

Use the CHeKT outdoor speaker to provide up to 120 decibel crystal clear announcements. This speaker connects to your network with a single LAN cable and can be assigned an IP address — allowing you to combine video and audio systems into a single proactive security solution. Once configured, you can respond immediately to emergency situations with live announcements or prerecorded messages. Utilizing automated rules, prerecorded messages can be prioritized to broadcast right away.

## Product Features

### IP67 Waterproof Design

For installation  
in outdoor settings

### 48K OPUS Audio Codec

Enables excellent  
sound quality

### Multi-Compatibility

Compatible with VoIP,  
SIP devices (IPPBX, IP Phone)  
via SIP

### IP Camera Compatible

Compatible with  
IP Camera VMS via ONVIF

### Pre-recorded Messages

Speaker supports  
pre-recorded messages

### HTTP API Support

Support HTTP API  
for alarm in transmit

# Specification

Audio	
Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
Speaker	
Max SPL	120dB
Frequency response	350Hz~8KHz
Frequency range	500-2KHZ ± 10dB 400-12KHZ ± 20dB
Harmonic distortion	0.1@1kHz
Signal to noise ratio	91dB
Network	
Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier	
Amplifier description	Built-in 30W Amplifier
Alarm	
Alarm output	1ch, When receiving a switch alarm, it can play a ringtone or a custom sound.
General	
Operating temperature	-30°C ~ +60°C
Operating humidity	5%~85%
Material	ABS (IP67 water-proof)
Rate power	30W
Power supply	POE or DC12V~24V
Installation	Wall mounted
Dimensions	285 x 205 x 290 mm
Net weight	2 KG
Languages	English
Warranty	2 years
Package contents	Network horn speaker

Specifications & designs are subject to change without prior notice.