

Features

- Selectable Rate of Rise and/or Fixed Heat Detector
- Low Profile
- Reliable Detection Technology
- LED Alarm Indicator
- Ambient Temperature Listing of 32°F to 150°F
- Simple DIP Switch Address Setting, No Programming Tool Required
- Magnetic Test Switch
- Product includes 5-year warranty
- UUKL Listed for Smoke Control



Description

The PAD300-HD is a listed analog addressable rate of rise and/or fixed temperature heat detector compatible with any fire alarm control panel that has the Potter Addressable Device (PAD) protocol. The heat sensing portion utilizes a proven thermistor for accurate and reliable heat detection. The detector and base (not included) are made of a durable plastic in an off-white to blend in with the ceiling.

The PAD300-HD is UL listed with a selectable fixed temperature point from 135° to 185° Fahrenheit and can be used for rate of rise applications. See detector spacing limitations below. This flexibility allows the installer to cover a wide variety of applications with a single unit.

The PAD300-HD and the control panel communicate over a proven and robust digital communication path and the system analyzes the information at the particular device. The total polling speed is less than five (5) seconds, well under the UL requirements.

The detector is compatible with any of the PAD300 series detector bases and simply twists on. The PAD300-HD is addressed using DIP switches in the rear of the detector and can be easily programmed in the field without special tools.

Setting the Address

Each addressable device on the SLC loop must have a unique address from 1 to 127 to function properly. The address is set using DIP switches.

Before connecting a device to the SLC loop, take the following precautions to prevent potential damage to SLC or device. Verify the following:

1. Power to the device is removed.
2. Field wiring is correctly installed.
3. Field wiring has no open or short circuits.

Technical Specifications

| | |
|--|--|
| Operating Voltage | 24 VDC |
| Detector Current Draw | 300 μ A |
| Alarm Indicator | 1 LED |
| Alarm Set-point Range | 135°F to 185°F (57°C to 85°C) |
| Rate of Rise Detection (Selectable Option) | 15°F/min. (8.3°C/min.) |
| Installation Temperature Range | 32°F to 150°F (0°C to 66°C) |
| Operating Relative Humidity Range | 0% to 93% (Non-condensing) |
| Start-up Time | Max. 1 sec. |
| Maximum Number of Addresses Per Loop | 127 |
| Maximum Number of Lighted Indicators in Alarm Per Loop | 30 |
| Color | Eggshell White |
| Weight (Without Base) | 68 g (2.4 oz) |
| Dimensions (Without Base) | Height: 1.5 in (38 mm) Diameter 3.93 in (100mm) |

Operation

The PAD300-HD is an analog addressable detector that uses one address on the Signaling Line Circuit (SLC) of a compatible fire alarm control panel. The unit communicates with the control panel as it is polled. The LED flashes every time the unit is polled and it will flash at a fast rate if the unit is in an active status. The polling LED can be turned off if desired for less conspicuous operation.

The PAD300-HD with the PAD300-4DB or PAD300-6DB has a low profile to blend into the surrounding environment. The system has a maximum of 30 LEDs that can be turned on simultaneously. If the system already has 30 LEDs on, the PAD300-HD will operate even though the LED will not illuminate.

Spacing

The ANSI/UL listed spacing limitations of PAD300-HD smooth ceiling are dependent on alarm set point.

| Alarm Set-Point | Rate of Rise Spacing | Fixed Temperature Spacing |
|----------------------------------|----------------------|---------------------------|
| 135°F to 185°F (57°C to 85°C) | Max. 70 ft. | Max. 70 ft. |

Compatible Bases

All bases will mount on a single gang, 3-1/2" octagon, 3-1/2" square, double gang, 4" octagon, 4" square, 50mm c/c, 60mm c/c and 70mm c/c boxes.

| Device | Description | Stock No. |
|-------------|--|-----------|
| PAD300-4DB | 4" Detector Base | 3992781 |
| PAD300-6DB | 6" Detector Base | 3992782 |
| PAD300-IB | 6" Base with an Isolator Module Included | 3992783 |
| PAD300-RB | 6" Base with One Form-C Relay Contact 2A @ 30VDC, 0.5A @ 125VAC | 3992784 |
| PAD300-SB | 6" Base with sounder module included. Sound pattern is provided from external source | 3992785 |
| PAD300-LFSB | 6" Base with 520Hz sounder module included. Sound pattern is provided from external source | 3992786 |

Ordering Information

| Model | Description | Stock No. |
|-----------|---------------|-----------|
| PAD300-HD | Heat Detector | 3993776 |