



iQLOCK-PG

PowerG Where it Matters



Better Range

Stable wireless communication over long range applications



High Strength

ANSI Grade 2 certifications brings extra security and piece of mind



Easy Installation

Easy configuration for smart locks with PowerG wireless communication



Attractive Styling

Three finish options to allow for the best style fit on different door colors



Reliable Connectivity

Reduce truck rolls by eliminating unstable wireless network connections

SPECIFICATIONS

| | |
|----------------------------------|--|
| Self-Handing | Supported |
| Bolt Type | Motorized / Standard deadbolt |
| Backset | 2 3/8" / 2 3/4" Adjustable (60/70mm) |
| Door Prep | 1 1/2" / 2 1/8" (38/54mm) |
| Door Thickness | 1 3/8" ~ 2 1/4" (35-58mm) automatic adjustment |
| Unlocking Method | PowerG wireless communication (via App and Panel), Button keypad, key, thumb-turn |
| Code Capacity | User code x 250 |
| Code Length | 4-10 digits |
| Override Key Cylinder | Yes |
| Cylinder | KW1 keyway |
| Working Voltage | DC 6V |
| Battery (Not included) | AA x 4 |
| Working Temperature | Exterior: -31°F to 150°F Interior: 32°F to 140°F |
| IP Rating | Exterior assembly: IP54 |
| Lockout Mode (Wrong entry limit) | Keypad lockout for 3 minutes after 10 entries of invalid user code |
| Low Battery Alarm | Yes |
| Battery Life | Min. 12 months (6 user code unlock events, and 10 unlocking and locking cycles for each day) |
| Certifications | FCC, IC, ANSI BHMA A156.36 Grade 2, UL10C (20min Fire Rating) |
| IoT Connection | PowerG |
| Product Weight | 1.6KG/PCS (3.6 LB) |
| Operating Humidity | Exterior: 100% condensing Interior: 20% – 95% non-condensing |