



UL22 is a shallow depth, lightweight, UL listed fire signaling device for mass notification & emergency communications. It provides superior voice intelligibility and high efficiency performance in a complete, 2' x 2' loudspeaker assembly. Components include: an 8" O.D., fire retardant loudspeaker with a 10 oz. magnet and a 4W, 25/70V rotary select transformer. The integral enclosure is 1,283 CID, molded fiber. The grille is perforated steel with four (4) seismic tie-off points in a white powder coat finish. A line supervision capacitor is included. No assembly required.



APPLICATION	Intended Use: Program Material: Installation:	Mass notification and emergency communications Signal tones and voice Fits into a 2' x 2' or 2' x 4' wide ceiling tile grid
AUDIO PERFORMANCE	Average Sensitivity Sound Pressure dB-SPL @10' per Tap: Loudspeaker Power Rating: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	1/4W = 78.7dB, 1/2 = 80.7, 1 = 81.5, 2 = 84.3, 4 = 87.4 20W RMS, EIA 426A Standard BeFe Ceramic, 10 oz. Nominal 60Hz - 17kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half space Dual Set of 6", Color-coded, Pre-cut and Tinned Leads
COMPONENT	Dimension: Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Integral Enclosure: Grille: Finish: Other:	3 1/2" (H) x 23 13/16" (W) x 23 13/16" (D) 7 lbs. 8C10PAFR 8" O.D. loudspeaker, 10 oz. magnet, fire retardant 4W, 25/70V, rotary select with 5 taps (0.25W, 0.50W, 1W, 2W, 4W) 1,283 CID, molded fiber Perforated steel with four (4) seismic tie-off points White powder coat finish A 10uF, 150V, line supervision capacitor is included
CERTIFICATION	UL Listed 1480 (UUMW) TYPE F UL Listed 2043 ASTM E84	When installed with supplied installation instructions and requirements of NEC/AHJ Suitable for use in air-handling spaces Includes integral backbox that meets/exceeds flame and smoke test w/ 3hr. burn rating
ADDITIONAL MODELS	UL22JB UL22DM	2' x 2' Tile Replacement Loudspeaker with 25/70V transformer, Built-In Junction Box 2' x 2' Tile Replacement Loudspeaker with 25/70V transformer, Built-In Device Mount

