Quam solution 3

The SOLUTION 3 is a complete, speaker/transformer/baffle/backbox/tile bridge assembly. It is designed for drop-tile ceiling installations but can also be used in hard ceilings using the included QMount bracket assemblies. The SOLUTION 3 includes two (2) of each of the following:

- 8" O.D., foam edge speaker with 10 oz. magnet and a 5W, 25/70V transformer
- round, steel, designer baffle
- · rust-resistant steel, load bearing support bridge
- round, steel, 275 CID backbox

AUDIO

PERFORMANCE

Each SOLUTION 3 includes two (2) complete speaker assemblies.



APPLICATION Intended Use: Indoor environment

Program Material:Paging, signal tones, and background musicInstallation:Downward-firing in a 24" wide, drop-tile ceilingHard Ceiling Install Option:Use the included QMount Bracket accessory

Average Sensitivity: 95dB SPL, 1W/1M

Loudspeaker Power Rating: 20W RMS, EIA 426A Standard Calculated Output: 102dB SPL, 5W/1M

Magnet Type & Weight:BeFe Ceramic, 10 oz. NominalFrequency Response:60Hz - 17kHz, EIA 426A StandardNominal Coverage Angle:90° Included Angle, -6dB/2kHz, Half Space

Audio Connection: 7", Color-coded, Pre-tinned Leads

COMPONENTBaffle Dimension:12 %" (Diameter) x $\%_6$ " (H)Backbox Dimension: $12 \%_6$ " (Diameter) x 4 %" (H)

Mounting Support Dimension: $23 \, \%'' \, (W) \times 14 \, \%_6'' \, (H) \times \%_6'' \, (D)$ Combined Weight: $15 \, \text{lbs}$.

Loudspeaker Model: 8C10FEPAX

Loudspeaker Specs: 8" O.D. foar

Loudspeaker Specs:8" O.D., foam surround, dual cone loudspeaker, 10 oz. magnetTransformer:TBLU: 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5W)

Baffle: BR8-2WS: round, steel

Finish: White powder coat finish on baffle

Backbox:ERD8U: round, steelMounting Support:SSB-6, rust-resistant steel

Hard Ceiling Brackets: QMount







