

SURFACE MOUNT LOUDSPEAKER

Quam SYSTEM 1

SYSTEM 1 is a complete loudspeaker system consisting of an 8" O.D., dual cone loudspeaker with a 5 oz. magnet and a 5W, 25/70V transformer mounted on a square, screw mount, steel baffle with a square, steel, vandal resistant, surface mount enclosure with four (4) 8-32 threaded inserts, a single 1/2" conduit entrance on the back and two (2) Wiremold knockouts. White powder coat finish.



APPLICATION	Intended Use: Program Material: Installation:	Indoor environment Signal tones, voice and music Horizontal or vertical surface mount
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Output: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	92dB SPL, 1W/1M 12W RMS, EIA 426A Standard 15W @ 8 Ohms 99dB SPL, 5W/1M BeFe Ceramic, 4.8 oz. Nominal 65Hz - 17kHz EIA, 426A Standard 90° Included Angle, -6dB/2kHz, Half Space 7" color-coded pigtails, pre-cut
COMPONENT	Dimensions: Weight: Loudspeaker: Transformer: Baffle: Backbox: Finish:	11 5/8" (H) x 11 5/8" (W) x 4 1/8" (D) 10 lbs. 8C5PAX TBLU: 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5.0W) BS8W SE1WVP with four (4) 8-32 threaded inserts White powder coat

