

## VANDAL RESISTANT LOUDSPEAKER

# Quam SYSTEM 1VP

SYSTEM 1VP is a complete, vandal resistant loudspeaker system consisting of an 8" O.D., moisture resistant loudspeaker with a 10 oz. magnet and a 5W, 25/70V transformer mounted on a square, stud mount, vandal resistant, steel baffle with a square, steel, vandal resistant, surface mount enclosure with four (4) 8-32 threaded inserts, a single 1/2" conduit entrance, and two (2) Wiremold knockouts. Three (3) interwoven, steel security screens are mounted between the faceplate and loudspeaker. Tamper resistant, 8-32 x 1" 'pin-in-torx' hardware included. White powder coat finish.



<b>APPLICATION</b>	<b>Intended Use:</b> <b>Program Material:</b> <b>Installation:</b>	Indoor or protected outdoor environment Signal tones, voice, and music Horizontal or vertical surface mount
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b> <b>Loudspeaker Power Rating:</b> <b>Calculated Output:</b> <b>Magnet Type &amp; Weight:</b> <b>Frequency Response:</b> <b>Nominal Coverage Angle:</b> <b>Audio Connection:</b>	94dB SPL, 1W/1M 20W RMS, EIA 426A Standard 101dB SPL, 5W/1M BeFe Ceramic, 10 oz. Nominal 80Hz - 8kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half Space 7", Color-coded, Pre-tinned Leads
<b>COMPONENT</b>	<b>Dimensions:</b> <b>Weight:</b> <b>Loudspeaker Model:</b> <b>Loudspeaker Specs:</b> <b>Transformer:</b> <b>Baffle:</b> <b>Security:</b> <b>Finish:</b> <b>Other:</b>	11 5/8" (H) x 11 5/8" (W) x 4 1/8" (D) 13 lbs. 8C10PAOT 8" O.D., moisture resistant loudspeaker TBLU; 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5W) BS8VP: square Three (3) interwoven, steel screens mounted between faceplate and loudspeaker White powder coat finish Tamper resistant, 8-32x1" 'pin-in-torx' hardware included

