

# Quam SYSTEM 2VP

SYSTEM 2VP is a complete, vandal resistant loudspeaker system consisting of an 8" O.D., moisture resistant loudspeaker with a 10 oz. magnet and a 5W, 25/70V transformer mounted on a square, stud mount, vandal resistant, steel baffle with a slanted, steel, vandal resistant, surface mount enclosure with four (4) 8-32 threaded inserts, a single 1/2" conduit entrance, and two (2) Wiremold knockouts. Three (3) interwoven, steel security screens are mounted between the faceplate and loudspeaker. Tamper resistant, 8-32 x 1" 'pin-in-torx' hardware included. White powder coat finish.



<b>APPLICATION</b>	<b>Intended Use:</b>	Indoor or protected outdoor environment
	<b>Program Material:</b>	Signal tones, voice, and music
	<b>Installation:</b>	Vertical surface mount, downward firing
<b>AUDIO PERFORMANCE</b>	<b>Average Sensitivity:</b>	94dB SPL, 1W/1M
	<b>Loudspeaker Power Rating:</b>	20W RMS, EIA 426A Standard
	<b>Calculated Output:</b>	101dB SPL, 5W/1M
	<b>Magnet Type &amp; Weight:</b>	BeFe Ceramic, 10 oz. Nominal
	<b>Frequency Response:</b>	80Hz - 8kHz, EIA 426A Standard
	<b>Nominal Coverage Angle:</b>	100° Included Angle, -6dB/2kHz, Half Space
	<b>Audio Connection:</b>	7", Color-coded, Pre-tinned Leads
<b>COMPONENT</b>	<b>Dimensions:</b>	11 5/8" (H) x 11 5/8" (W) x 5 3/8" (D)
	<b>Weight:</b>	13 lbs.
	<b>Loudspeaker Model:</b>	8C10PAOT
	<b>Loudspeaker Specs:</b>	8" O.D., moisture resistant loudspeaker
	<b>Transformer:</b>	TBLU; 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5W)
	<b>Baffle:</b>	BS8VP: square
	<b>Security:</b>	Three (3) interwoven, steel screens mounted between faceplate and loudspeaker
	<b>Enclosure:</b>	SE2WVP
	<b>Finish:</b>	White powder coat finish
	<b>Other:</b>	Tamper resistant, 8-32x1" 'pin-in-torx' hardware included

