

Quam SYSTEM 5VC

SYSTEM 5VC is a complete, shallow depth, lightweight, 1' x 2' ceiling tile replacement loudspeaker system consisting of an 8" O.D., dual cone loudspeaker with a 5 oz. magnet and a 5W, 25/70V transformer with screwdriver or knob adjusted volume control. The molded fiber enclosure is 617 CID. The SYSTEM 5VC has a powder coated steel baffle with standard perforation and four (4) seismic tie-off points. The cable clamp and one (1), 24", "T" rail are included. No assembly required.



APPLICATION	Intended Use: Indoor environment Program Material: Signal tones, voice, and music Installation: Mounted parallel to floor plane in a 24" wide suspended ceiling grid
AUDIO PERFORMANCE	Average Sensitivity: 92dB SPL, 1W/1M Loudspeaker Power Rating: 12W RMS, EIA 426A Standard Maximum Power Rating: 15W @ 8 Ohms Calculated Output: 99dB SPL, 5W/1M Magnet Type & Weight: BeFe Ceramic, 5 oz. Nominal Frequency Response: 65Hz - 17kHz, EIA 426A Standard Nominal Coverage Angle: 100° Included Angle, -6dB/2kHz, Half Space Audio Connection: 4", Color-coded, Pre-tinned Leads
COMPONENT	Dimension: 3 1/2" (H) x 23 13/16" (W) x 11 13/16" (D) Weight: 3.90 lbs. Loudspeaker Model: 8C5PAX Loudspeaker Specs: 8" O.D. loudspeaker, 5 oz. magnet Transformer: TBLU; 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5W) Integral Enclosure: 617 CID molded fiber Grille: Standard perforated steel with four (4) seismic tie-off points Finish: White powder coat finish

