


14/2 PLENUM RATED, UNSHIELDED FIRE ALARM CABLE



14 AWG 2 SOLID CONDUCTORS

Ratings FPLP, CL3P, FT6
Approvals ETL Listed



Construction

Conductor 14 AWG Solid Bare Copper
Conductor Count 2
Insulation Plenum PVC (0.007" nom.)
Insulation Colors Black, Red
Lay Length 5.25" nom.
Shielding N/A
Rip Cord Yes
Jacket Plenum PVC (0.015" nom.)
Overall Diameter 0.206" nom.
Print Legend ADI PRO P/N RN-200XXXX
OXYGEN FREE 2C14 3180662 (ETL)US
FPLP 75C ROHS CL3P FT6 LOT#XXXX
MMDDYY XXXXFT

Properties

Operating Voltage 300 Volts max.
DC Resistance 2.57 Ohms/1000' at 20°C
Capacitance 22.2 pF/ft.nom.
Temperature Wire maintains flexibility between -20°C/-4°F to 75°C/167°F. Exposure below 0°C/32°F may cause PVC jacket to be brittle or crack if impacted or bent.
Flame Rating NFPA 262 (Plenum); CSA C22.2 No. 2556 (FT6)
RoHS Compliant Yes
Country of Origin China

PART#	COLOR	LENGTH	BOX
RN-2001106	Red	1000Ft.	Wood Reel
RN-2003506	Red	500Ft.	Wood Reel



For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands