


STRANDED GENERAL PURPOSE CABLE


22/2 CM/CL2 UNSHIELDED

ADI PRO

SPEC SHEET



RT-8000501



RT-8005101

Physical Characteristics

Standard Compliance: UL444/UL13

Certifications UL: E507576-PYV OR E535998

Conductor: 22 AWG Bare Annealed Copper

Insulation: PVC

Conductor Color Code:

- 1: Red
- 2: Black

Rip Cord: Applied longitudinally under jacket

Jacket: PVC

OD: 3.0mm

Jacket Legend:

ADI PRO P/N 2C 22AWG E507576-PYV C(UL)US CM OR E535998 CL2 75C RoHS

Properties

Operating Voltage: 300 Volts max.

DC Resistance: 17.5 Ohms / 1000 ft. at 20°C

Capacitance: 480PF


Conductor Resistance: 54.3Ω/KM

Temperature: -20°C to 60°C

Flame Rating: UL 1685 Vertical Tray

RoHS Compliant: Yes

Country of Origin: VIETNAM



Part#	Color	Length
RT-8000501	White	500' Speed Coil
RT-8005101	White	1000' Express Reel Box



RoHS



For more information contact your ADI Sales person or visit adiglobal.com/adiexclusivebrands