STI WIRELESS CHIMES



STI-3610



STI-3360

PRODUCT OVERVIEW

STI Wireless Chimes greet your visitors with a pleasant chime and lets you know when the door opens or a person enters the detection zone. All chimes are compatible with each other. Distinguish between front and back doors by adding transmitters and selecting a different chime on each. Transmitters have up to 500' operating range (line of sight).

HOW IT WORKS

Wireless Doorbell Chime (STI-3350)

STI-3350

Mount the wireless button next to your door, plug the receiver into any 120 VAC indoor electrical outlet and the chime is ready to operate. Doorbell button is water-resistant.

Wireless Entry Alert® Chime (STI-3360)

Mount the small transmitter and magnet to any door and plug the receiver into any 120VAC indoor electrical outlet. That's it. No wiring required. When a monitored door opens, the Entry Alert Chime sends a signal to the receiver announcing the entrance with one of ten selectable chimes.

Wireless Motion-Activated Chime (STI-3610)

Mount the motion transmitter and plug chime receiver into any 120VAC indoor electrical outlet within operating range. Alerts when someone enters the transmitter's detection zone. The weather sealed transmitter has 140° x 40 ft. detection zone. Includes adjustable mounting bracket.

Wireless Doorbell Extender (STI-3300)

This doorbell chime connects to your existing traditional hard wired doorbell system and extends a new chime to hard-to-hear areas. Once the unit is wired into existing system, the included receiver can be plugged into any standard 120VAC indoor electrical outlet. This allows you to hear when someone is at your door when in remote areas. Normally open switch, 16 VAC.

KEY FEATURES

General Information

- All chimes are compatible with each other.
- Add up to 10 transmitters per receiver.
- Up to 500' operating range (line of sight).
- · Ideal for the home, store or office.
- · One year limited warranty.

Construction

· UL/cUL Listed, FCC and IC Certified.

Installation

- · Quick and easy to install no wiring needed.
- Receiver plugs into 120 VAC outlet. Electronics
- Receiver has a low and high volume adjustment.
- · Supervised low battery alert.

Options

- 10 sound options with the push of a button on the transmitter (excludes STI-3331).
- STI-3300 can distinguish between a front and back door by adding another sensor. The first doorbell will play "ding-dong" and the second will play "dong."



STI Wireless Chimes

Dimensions and Technical Information

MODELS AVAILABLE

STI-3350	Wireless Doorbell Chime with Receiver
STI-3360	Wireless Entry Alert [®] Chime with Receiver
STI-3610	Wireless Motion-Activated Chime with Receiver
STI-3300	Wireless Doorbell Extender with Receiver

Accessories

STI-3301	Wireless Doorbell Chime Transmitter
STI-3551	Wireless Entry Alert® Transmitter
STI-3601	Wireless Motion-Activated Transmitter
STI-3331	Wireless Doorbell Extender Transmitter
STI-3353	Wireless Chime Receiver

Selectable Sounds (excludes 3300/3331)

Ding Dong Ding-Dong Westminster - 4 note Westminster - 8 note Knock Knock Jingle Bells Barking Dogs **Bicycle Bell** Buzzer

SPECIFICATIONS 433 MHz Frequency:

WARRANTY

TESTING

Power Source: Receiver plugs into 120 VAC outlet (minimum 110 VAC)

Sensors include: STI-3301 One CR2032 battery STI-3551 One AAA battery STI-3601 One Lithium CR123 battery STI-3331 n/a

APPROVALS & WARRANTY

· UL/cUL Listed No. S7255

· FCC and IC Compliant

It has been tested and approved or listed by:

One year limited warranty within normal use.



All accessories work together! Make each a different sound and know the exact transmitting source.



Safety Technology International

2306 Airport Road info@sti-usa.com Waterford, MI www.sti-usa.com 48327, USA Tel:248-673-9898

Taylor House 34 Sherwood Rd., Bromsgrove, www.sti-emea.com Worcs., B60 3DR, England

info@sti-emea.com Tel: +44 (0) 1527 520 999 Unit 7A Lockheed Avenue Airport Business Park Waterford X91 HWF2 Ireland