

## 15W IP Ceiling Speaker

**SPIPC6A**

**SPIPC6AM** Includes mic input

### Features

- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- Two-way audio support with mic input\*
- PoE or 12/24VDC

\*SPIPC6AM only



### Audio

Codec	OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz
-------	--

### Speaker

Max Sound Pressure Level	96dB
Frequency Response	100Hz~18kHz
Frequency Range	500-2KHZ ± 10dB 400-12KHZ ± 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

### Network

Security	Password protection, IP address filtering, digest authentication, user access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

### Amplifier

Amplifier Description	Built-in 15W Amplifier
-----------------------	------------------------

### Microphone

Built-in MIC	SPIPC6A: No	SPIPC6AM: Yes
--------------	-------------	---------------

### General

Material	Metal
Rate Power	15W
Power Supply	PoE or 12-24V
Dimensions	7.9" (Dia.) x 3.5" (D)
Net Weight	2.2 lbs
Package Includes	Network Ceiling Speaker User Manual

