

15W IP Horn Speaker

SPIPH8A

Features

- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- IP67 waterproof design is ideal for outdoor installations
- PoE or 12/24VDC



Audio

Codec	OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz
-------	--

Speaker

Max Sound Pressure Level	113dB
Frequency Response	300Hz~8kHz
Frequency Range	500-2kHz ± 10dB 400-12kHz ± 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Network

Security	Password protection, IP address filtering, digest authentication, user access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description	Built-in 15W Amplifier
-----------------------	------------------------

General

Operating Temperature	-22° F - 140° F
Operating Humidity	5% - 85%
Material	ABS (IP67 waterproof)
Rate Power	15W
Power Supply	PoE or 12-24V
Dimensions	8.86" (W) x 6.5" (H) x 9.45" (D)
Net Weight	2.87 lbs
Package Includes	IP Horn Speaker User Manual
Color	White

