SimpliShare™
4K Presentation Adapter Cable

SSH-500T

User Manual

Overview:
The SimpliShare™ SSH-500T 4K Presentation Cable is the perfect solution for office, huddle space and conference room applications. It allows connection for various devices that come with USB-C, HDMI or Mini DisplayPort video output to any HDMI 4K display or projector.

How to use:
- Plug one of any of the three input connection cables into your computer, either USB-C, HDMI or Mini-DP, then plug the output HDMI cable into your display or projector.
- Plug the attached USB-A cable to a DC 5V power supply from either TV display or USB wall charger.
- **Optional**: When you have three devices all plugged in simultaneously to the cable, the display priority order is USB-C, HDMI, and then mini DisplayPort.

Specifications:
- HDMI Input: 4K @60Hz (3840x2160)
- HDMI Output: 4K @60Hz (3840x2160)
- Mini DisplayPort Input: 4K @60Hz (3840x2160)
- USB Type-C Input: 4K @60Hz (3840x2160)
- Power Requirements: DC 5V

Connections:
Input:
- x1 USB Type-C Male (12 inches)
- x1 HDMI Male (12 inches)
- x1 Mini DisplayPort Male (12 inches)
- x1 Detached USB-A power cable (18 inches)

Output:
- x1 HDMI male (4ft 11in)

Note: The attached USB-A cable must be powered using a 5V USB adapter or can be powered if your display has a supporting USB port.

System Compatibility:
- Windows® 8 & 10
- Mac® OS X, 10.6, 10.7, 10.8, 10.9
- Android™ 8.0 or above
- iOS® 12.3, 12.4
- iPad® OS 13.0 & up

What's in the Box?
- x1 SimpliShare™ USB-C, HDMI & Mini DisplayPort to 4K HDMI Presentation Cable
- x1 USB-A to Micro-B cable (Optional to supply power to the source end)
- x1 User Manual