



SW2200AC

| | | |
|------------------------|-------------------------|---------------|
| Resolution | Standard 600TVL | Hi-Res 700TVL |
| Min Illumination | 0.1 Lux | 0.8Lux |
| S/N Ratio | ≥48dB | |
| Video Output | 1.0Vp-p/75Ω | |
| White Balance | Auto | |
| Backlight Compensation | Auto | |
| Electronic Shutter | 1/50 (1/60) ~ 1/1000000 | |
| Gamma Correction | 0.45 | |
| Lens | 3.7mm | |
| Power Consumption | 12Vdc 150mA | |

Wireless

| | | |
|----------------------|---------------------|----------------------|
| | Standard | Hi-Power |
| Max TX Output | 10dBm | 100mW |
| Power Consumption | 12Vdc @ 150mA | 12Vdc @ 300mA |
| Useable Channel | 4 | 80 |
| Receiver Sensitivity | -80dBm min | -80dBm min |
| Operating Range | 700ft Line of sight | 1500ft Line of sight |

DVR

| | |
|-------------------|---|
| System | NTSC |
| Codec | Mpeg4-SP ASF File Format |
| Record Frame Rate | Selectable up to 30FPS |
| Record Quality | Low/Med/High |
| Time/Date | Overlay with Video Images in ASF File |
| Input | From Built-in Camera |
| Output | 1Ch composite Video Line Out, 1Vp-p/75Ω |
| Storage Device | SD Card (up to 32Gb), 8GB included |
| Record Mode | Manual, Schedule (alarm, motion detection, continues) |
| Playback Speed | 1X, 2X, 4X, 8X, 16X, 32X |