



SW2600DVR

Standard Function		
Video	System	NTSC/PAL Video System and Video Loss Auto Detection
	Codec	Mpeg4-SP ASF file Format
	Record Frame Rate	1,2,....., Maximum FPS selectable Maximum: 30 fps @ 320 x 240/ 12 fps @ 640 x 480
	Record Quality	Low/Medium/High
	Recoding Date/Time	Overlay with Video Images in ASF file
	Input	From Built-in Camera
	Output	1 CH composite Video Line Out
Cam	Resolution	Sony CCD 600VL, .001Lux
	Lens	3.7mm Pinhole Lens
Storage Device		SD Card (up to 32GB) 8gb Included
Recording Mode		Schedule (Alarm / Motion Detection / Continue)
Motion Detection Setting		Multiple Blocks and Adjust Sensitivity
Event Search Function		Property and First Image of Selected File is displayed
Playback Speed		x1 / x2 / x4 / x8 / x16 / x32
Power Supply		12Vdc, 1Amp
Dimensions		4 ½ x 4 ½ x 4 ¾
Operating Environment		30%~80% RH, 41 degrees F – 113 degrees F
Storage Environment		30% ~ 90% RH, 32 degrees F -122 degrees F



SPERRY WEST

Sperry West Inc.
5575 Magnatron Boulevard
San Diego, California 92111

e-mail spyder@sperrywest.com
web site www.sperrywest.com

Spyder is a registered trademark of Sperry West Inc.