HTINT591T

3.6mm fixed lens, dark grey housing

HTINT601T

3.6mm fixed lens, dark grey housing

Intensifier® T HD-TVI 1080p 2MP Dome Camera














- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator • Built-in heater and anti-fog glass reduces
- condensation under any weather condition
- Additional analog output for 960H • 3-axis for wall and ceiling mounting

59PLATE

- Chameleon Cover™: snaps on and can be painted to match any décor!*
- Full OSD operation through on-board control and UTC (up the coax)
- Signal distance up to 1600 feet**
- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant
- 5 year warranty

paintable, snap-on Chameleon Cover™

24VAC

12VDC

Power Supply

Intensifier® T HD-TVI 1080p 2MP Turret Camera













- Full HD resolution over coax (HD-TVI) • Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- Built-in heater and anti-fog glass reduces condensation under any weather condition
- 3-axis for wall and ceiling mounting

- Full OSD operation through on-board control and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant

Additional analog output for 960H Signal distance up to 1600 feet**

- 5 year warranty







(use with

INTWM only)



(use with 60PLATE)





60PLATE

and CVCJBD)



specotech.com • 800.645.5516 • Fax: 631.957.9142 • sales@specotech.com





HTINT70T 2.8–12mm auto iris varifocal lens.

• Full HD resolution over coax (HD-TVI)

• Supports up to Full HD 1080p @ 30fps

• Amplify existing light with no distance limitation

• Built-in heater and anti-fog glass reduces

• 3-axis for wall and ceiling mounting

condensation under any weather condition

• Presets: Indoor, Outdoor, Low Light, Lobby, Elevator

Superior low-light performance

HD INT WDR FULL AND HEATER IP67

dark grey housing

• True WDR operation

HTINT701T

Intensifier® T HD-TVI 1080p 2MP Bullet Cameras

3.6mm fixed lens, dark grey housing

• Full OSD operation through on-board

control and UTC (up the coax)

Vandal / tamper resistant

• IP67 compliant

5 year warranty

• Additional analog output for 960H

• Signal distance up to 1600 feet**

• 12VDC & 24VAC dual voltage operation

CVC6246T

2.8–12mm auto iris varifocal lens. white housing

2.8–12mm auto iris varifocal lens.

CVC6246TW

Intensifier® T HD-TVI 1080p 2MP Indoor Dome Cameras



black housing











- Full HD resolution over coax (HD-TVI)
- Amplify existing light with no distance limitations
- No problems caused by objects that reflect or absorb IR light sources
- Presets: Outdoor, Indoor, Elevator, Lobby, Hallway & Dark
- 12VDC / 24VAC dual voltage operation
- Full OSD operation via UTC
- 3-axis wall or ceiling mount • Signal distance up to 1600 feet*
- Additional analog output for 960H
- 5 year warranty



Optional Accessories



Square

Junction Box

















Power Supply







Wall Mount



Optional Accessories







Adaptor Plate

Optional Accessories

Corner/Pole

(use with

Intensifier

HD

ameras

HT5940T

2.8–12mm auto iris varifocal lens

3.6mm fixed lens, dark grey housing

HT5941T

VLD2TW

3.6mm fixed lens, white housing 3.6mm fixed lens, dark grey housing HT71TG

HT71TW

2.9mm fixed lens, dark grey housing

HD IR FULL *)
DAY
NIGHT IP66

• Full HD resolution over coax (HD-TVI)

• Compact size – only 2.36" in diameter!

• Weather / Vandal resistant operation

Additional analog output for 960H

Cast aluminum construction

• 12 IR LEDs

HD-TVI 1080p Color Mini-Turret Camera

2.9mm fixed lens, white housing

HD-TVI Intense IR 1080p 2MP Dome Cameras



dark grey housing











- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- True day/night operation mechanical IR cut filter
- Built-in heater and anti-fog glass reduces condensation under any weather condition
- 3-axis for wall and ceiling mounting

- painted to match any décor!*

- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant

• Chameleon Cover™: snaps on and can be

- Full OSD operation through on-board control and UTC (up the coax)
- Additional analog output for 960H







paintable, snap-on Chameleon Cover™

Optional Accessories





(use with 59PLATF)









INTWM only)















Power Supply

HD-TVI 1080p IR Dome Camera









- Full HD resolution over coax (HD-TVI)
- 24 built-in IR LEDs
- Supports up to Full HD 1080p @ 30 fps
- 3-axis for wall and ceiling mount
- Adaptor plate for optional accessories included
- Additional analog output for 960H
- 12VDC operation (power supply not included)
- IP66 compliant
- 2 year warranty

Optional Accessories





Signal distance up to 1600 feet*



specotech.com • 800.645.5516 • Fax: 631.957.9142 • sales@specotech.com

HD-TVI Intense IR 1080p 2MP Turret Camera



• 28 built-in IR LEDs

• True WDR operation



• Full HD resolution over coax (HD-TVI)

• Supports up to Full HD 1080p @ 30fps

• Intense IR function — no saturation, IR intensity

• True day/night operation — mechanical IR cut filter

adapts to subject to provide vivid image

• Built-in heater and anti-fog glass reduces

HT6041T













- Full OSD operation through on-board
- Additional analog output for 960H
- Signal distance up to 1600 feet*
- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant
- 5 year warranty

- 3-axis for wall and ceiling mounting
- control and UTC (up the coax)

condensation under any weather condition

Optional Accessories

(use with

INTWM only)





60PLATE

and CVCJBD)



Corner/Pole Adaptor











12VDC



 Signal distance up to 1600 feet* Full OSD operation via UTC

- IP66 compliant
- 12VDC required • 5 year warranty



Optional Accessory



12VDC

*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. **To preserve signal quality and distance. Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield.

Cameras