

TF-BFE5A11D

5MP Panoramic Fisheye Network Camera

KEY FEATURES

- ✓ 5MP Native Sensor Resolution
- ✓ Edge Dewarp with Panoramic & 4-PTZ Modes
- ✓ Low Light with Surround IR LED Supplemental Lights
- ✓ IP66 Water Resistance
- ✓ IK10 Vandal Resistance



SPECIFICATIONS

| VIDEO | |
|---------------------|---|
| Image Sensor | 1/2.7" Progressive CMOS Raw Fisheye Mode*: 5MP |
| Effective Pixels | 4PTZ Mode: 1920x1920 Max Panoramic Mode: 1920x1080 Max |
| Frame Rate | 30 FPS Max |
| Lens | Focal Length 1.1mm, F2.4 |
| Day and Night | Mechanical IR-Cut Filter |
| WDR | True WDR |
| Compression | H.265**/ H.264/ MJPEG |
| AUDIO | |
| Compression | G.711/ G.726/ AAC/ LPCM |
| Streaming | 2 way |
| Audio Input | Line-In, 3.5mm Jack Outdoor |
| Audio Output | Line-Out, 3.5mm Jack Outdoor |
| NETWORK | |
| Interface | RJ45 10/100Mbps Ethernet |
| Security | User Authentication/HTTPS/IP Filter/IEEE 802.1x |
| Supported Protocols | ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS |
| INTEGRATION & EVENT | |
| ONVIF | Profile S/ G/ Q/ T conformant |
| Analytics | Motion Detection/ Tampering/ Audio detection |
| Event Triggers | External Input, Analytics, Network Failure Detection, Periodical Event, Manual Trigger |
| Event Actions | External output Activation Video and audio recording to edge storage File Upload : FTP, network share and email Notification : HTTP, FTP, email |
| Supported NVR | Turing Smart Series (ONVIF) |
| Turing Vision | Limited support with Turing Legacy Core Consult Turing representative for details |

| POWER | |
|---------------------|--|
| Power | DC12V±25%,PoE (IEEE 802.3af) Power consumption: Max. 8.5W |
| Power Interface | Ø 5.5mm coaxial power plug |
| GENERAL | |
| Dimensions (Φ × H) | Φ125 × 43.7 mm (Φ4.9" × 1.7") |
| Weight | 0.79lb (0.36kg) |
| Working Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| surge protection | 4KV |
| Reset Button | Supported |
| Protection | Ingression protection: IP66 Vandal resistant: IK10 |
| VIDEO DEWARP | |
| 4 PTZ | Up to 1920x1920 pixels 4 views combined into one stream Angles adjustable on web interface |
| Panoramic | Up to 1920x1080 pixels |
| Fisheye View | Up to 1920x1920 pixels Not dewarp-able on Turing Vision or Smart NVR |
| 2 PTZ | Up to 1920x1080 pixels 2 views, front and back, combined into one stream |

MOUNTING ACCESSORIES



C-BA1-00
Double & square gang box adapter plate



TF-BPDCPR
Pendant cap w/ 1.5" NPT
Compatible with:

- Wall Mount: TP-PCWM
 - Corner Mount: TP-PCCM (requires TP-PCWM)
 - Pole Mount: TP-PCPM (requires TP-PCWM)
- Pendant Mount: TP-PCPDMB
 - 7.87" (200 mm) Extension: TP-PCPDM2 (requires TP-PCPDMB)
 - 19.69" (500 mm) Extension : TP-PCPDM5 (requires TP-PCPDMB)
- Parapet Mount: TP-PCPRM

