

Eaton ELSPSTW-AL

Catalog Number: ELSPSTW-AL

Eaton Eluxa high fidelity speaker strobe, LED, wall, white, ALERT, clear lens, 15/30/75/110/135/185 cd, 25/70V, indoor

General specifications

Product Name	Catalog Number
Eaton Eluxa high fidelity speaker strobe	ELSPSTW-AL
UPC	Product Length/Depth
786697010514	6.35 in
Product Height	Product Width
2.94 in	4.56 in
Product Weight	Warranty
1.44 lb	3 year
Compliances	Certifications
Not Applicable	Contact Manufacturer



Product specifications

Mounting Method

Wall

Housing color

White

Indoor/outdoor

Indoor

Housing material

Plastic

Lettering

ALERT

Voltage

24 V

25 V

70 V

Operating Temperature

32°F to 122°F (0°C to 50°C)

Compliance and standards

UL

ULC

FCC

Strobe specifications

Lamp type

LED

Candela settings

15 cd

30 cd

75 cd

110 cd

135 cd

185 cd

Current draw (DC)

0.022

0.030

0.060

0.086

0.125

0.185

Lens color

Clear

Lens material

Lexan

Speaker specifications

Frequency range - min

300 Hz

Frequency range - max

8000 Hz

Sound level (dBA)

75/79/82/85/87

Taps (Selectable)

1/8, 1/4, 1/2, 1, 2

Resources

Brochures

[Eluxa family brochure](#)

[Eluxa product cross reference](#)

Catalogs

Wheelock life safety notification appliances catalog CA450001EN

Drawings

Eluxa speaker strobe ceiling drawing

Eluxa speaker strobe wall drawing

Installation instructions

Eluxa speaker wall install sheet P85757

Eluxa speaker ceiling install sheet P85758

Selling policy and T&Cs

Eluxa UL listing

Technical data sheets

Eluxa high fidelity speaker data sheet

Eluxa high fidelity amber lens speaker strobes data sheet

wheelock-mounting-accessories-data-sheet



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)