



RRN series rails are tapped to accept threaded 10-32 screws (RRN-24 shown).




Mounting rails accept threaded 10-32 screws and feature a printed scale showing rack unit increments to facilitate set-up. The 1U position should be placed at the bottom of the rack to facilitate consistent loading of equipment. Rails are made from sturdy 11-gauge steel and have a black semi-gloss finish.

### FEATURES

- For use with Lowell rack series LGNR and LGVR
- Fixed hole positions
- Black semi-gloss finish
- Made in the USA with 100% certified US steel
- Printed RU increments to aid equipment mounting
- Includes mounting hardware
- Sold in pairs

### A & E SPECIFICATIONS

Additional mounting rails for the rack shall be Lowell Model No. \_\_\_\_\_. The rails shall be fabricated from 11-gauge steel and have a black semi-gloss finish. Each rail shall measure \_\_\_ rack units and be tapped on one side to accept threaded 10-32 screws. The rails shall also feature a printed scale showing rack unit increments.



TOP VIEW

### RRN SERIES SUMMARY

Model No.	Description	Hardware Included	Overall Height in [mm]	RU	Quantity
RRN-24	Rack Mounting Rails	Yes	42.00 [1067]	24U	1-pr.
RRN-37	Rack Mounting Rails	Yes	64.75 [1645]	37U	1-pr.
RRN-40	Rack Mounting Rails	Yes	70.00 [1778]	40U	1-pr.
RRN-44	Rack Mounting Rails	Yes	77.00 [1956]	44U	1-pr.

One rack unit (RU or U) = 1.75 inches or 44.45 mm.

