

External 192V 3U Rack/Tower Battery Pack for select Tripp Lite UPS Systems (BP192V12-3U)

MODEL NUMBER: BP192V12-3U











Highlights

- Extends the runtime of expandable 192V DC Tripp Lite UPS Systems
- Included daisychain connector supports the addition of multiple compatible external battery packs
- Supports 3U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount and tower installation available

Package Includes

- BP192V12-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Description

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU12KRT4UHW, SU5000RT4U, SU5000RT4UHV, SU5000RT4UTF, SU6000RT4U, SU6000RT4UHV, SU6000RT4UHVG, SU6000RT4UHVHW, SU6000RT4UTF, SU6000RT4UTFHW, SU8000RT4U and other Tripp Lite UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation

Specifications

OVERVIEW		
UPC Code	037332125903	
INPUT		
UPS Input Cord Length (ft.)	3	



UPS Input Cord Length (m)	0.9	
Input Phase	Single-Phase	
ОИТРИТ		
Overload Protection	50A DC output fuse	
BATTERY		
Expandable Battery Runtime	Includes a second input/output connector to daisy-chain multiple battery packs	
Expandable Runtime	Yes	
DC System Voltage (VDC)	192	
UPS Connection	Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)	
Typical Battery Lifespan	4-6 years typical (North America)	
PHYSICAL		
Material of Construction	Steel	
Rack Height	3U	
External Battery Pack Form Factor	Rack/Tower	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount	
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2POSTRMKITHD); Tower (2-9USTAND)	
Minimum Required Rack Depth (cm)	91.44	
Minimum Required Rack Depth (inches)	36	
Shipping Dimensions (hwd / in.)	11.00 x 23.00 x 33.00	
Shipping Dimensions (hwd / cm)	27.94 x 58.42 x 83.82	
Shipping Weight (lbs.)	205.83	
Shipping Weight (kg)	93.36	
Unit Dimensions (hwd / in.)	5.250 x 17.500 x 28.000	
Unit Dimensions (hwd / cm)	13,3 x 44,5 x 71,1	
Unit Weight (lbs.)	174.00	
Unit Weight (kg)	78.93	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe)	
WARRANTY & SUPPORT		



Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.