

# 3G ULTRA 718 Wallplate Transmitter

Just Add  
**Power**

VBS-HDIP-718WP4

## Dolby Digital 5.1 Downmix with Stereo Out, USB & VGA Wallplate



The 3G Ultra 718WP4 Wallplate Transmitter fits into a 4-gang construction box and provides multiple video and audio inputs and outputs to any Just Add Power video distribution system.

Distribute Dolby Digital 5.1 audio to every zone and transform to stereo audio for 2-channel zones. Mix-and-match the 3G Ultra 718WP4 Transmitter with any 3G Ultra or 2G Omega models to distribute any source to any zone.

### Features


<b>Audio</b>	Dolby 5.1 Downmixing  Stereo Audio Output 3.5mm	<b>KVM Support</b>	Provide local and remote access to all computers on the system with a built-in keyboard, mouse and touchscreen interface at both ends of a connection
<b>Colors</b>	Black, White or Custom	<b>Scalability</b>	Fully compatible with all 3G Ultra and 2G Omega products
<b>HDCP 2.2 Support</b>	Display content with HDCP 2.2 copy/content protection on any HDMI screen in system		

# 3G ULTRA 718 Wallplate Transmitter


VBS-HDIP-718WP4

Just Add  
**Power**

## Front of Device:



## Side of Device:



All measurements in millimeters (mm)

## Specifications

<b>Bandwidth</b>	180-500 Mbps	<b>POE</b>	10 watts maximum
<b>Compliance</b>	HDCP 2.2 RoHS/FCC/CE	<b>Ports</b>	Gigabit Ethernet HDMI In HDMI Out 3.5mm Line-In 3.5mm Mic-In 3.5mm Stereo Out DB9F RS232 w/ null modem DB9M Service port Micro-USB 2.0 5.5mm/2.1mm barrel
<b>Dimensions &amp; Weight</b>	108 x 184 x 79.5 mm 4.3" x 7.2" x 3.1" inch 0.27kg / 0.6 lb	<b>Power Supply (not included)</b>	~4.7-23V 5.5mm/2.1mm, Positive tip
<b>Encryption</b>	Hardware-Based AES 256-bit Encryption of network video signal	<b>Supported Resolutions</b>	Up to 4096x2160 (interlaced & progressive)
<b>Operating Temp</b>	0-60 °C / 32-140 °F		

## Specifications

### Encoding/Decoding

<b>Video Codec</b>	AGIC-G1 Proprietary Visually Lossless Video Codec
<b>Audio Codec</b>	Proprietary I2S Lossless Audio Codec
<b>Bit Rates</b>	300 to 850 Mbps
<b>Latency</b>	Ultra-low latency 16ms @ 1080p60 & 720p60 33ms @ 4K30
<b>Streaming Protocols</b>	IP, UDP, TCP, ICMP, IGMP
<b>Copy Protection</b>	HDCP 2.2, AES-128 Encryption

### Video

<b>Maximum Resolutions</b>	High Dynamic Range HDR10 4K30 4:4:4 HDR 8-bit 4K30 4:2:0 HDR 12-bit 1080p60 4:4:4 HDR 12-bit
<b>Input Signal Types (Encoder)</b>	HDMI
<b>Output Signal Types</b>	HDMI
<b>Scaler (Decoder)</b>	720p up to 4K30 with many options inbetween

### Audio

<b>Input Signal Types</b>	HDMI, Analog Stereo
<b>Output Signal Types</b>	HDMI, Analog Stereo
<b>Digital Formats</b>	Dolby Atmos, DTS:X, Dolby TrueHD, DTS-HD, Dolby Digital, Dolby Pro Logic, DTS, LPCM up to 8 channels
<b>Analog Formats</b>	Stereo 2-channel up to 96 kHz

### Power

<b>Power Consumption</b>	10 watts maximum during operation 0 watts when idle
--------------------------	--

### Compliance

CE, FCC, RoHS

### Communication & Control of External Devices

<b>Ethernet</b>	1Gb RJ-45 for control and AV
<b>USB</b>	USB 2.0
<b>Serial/RS-232</b>	Bi-directional control and monitoring
<b>HDMI</b>	CEC, EDID (Transmitter)
<b>Infrared (IR)</b>	Available with add-on

### Connectors

<b>LAN</b>	8-pin female RJ-45 1000Base-T POE (802.3af)
<b>HDMI Input</b>	HDMI Type A female
<b>HDMI Outputs (Transmitter loopout &amp; Receiver output)</b>	HDMI Type A female
<b>RS232</b>	3.5mm female
<b>Stereo Output</b>	3.5mm female
<b>USB (Receiver)</b>	USB Type-A female (x2)
<b>USB (Transmitter)</b>	Micro-USB female (x1)

### Environmental

<b>Cooling</b>	Convection / no fan (no moving parts)
<b>Temperature</b>	0-60 C / 32-140 F
<b>Heat Dissipation</b>	34 BTU/hr
<b>Acoustic Noise</b>	0 dBA