

# New Product Introduction

# ADI PRO

## ADI PRO Mortise All-In-One Fire Rated Strike



EXCLUSIVE  
@ADI

### Applications:

ADI PRO's Mortise all-in-one fire rated strike is compatible with all standard mortise and cylindrical locksets. This versatile electric strike delivers unparalleled security and adaptability, featuring five robust stainless steel faceplates and ANSI standard, Grade 1 certification.

### Features:

- Fire rated for a high level of protection in emergencies
- Compatible with mortise and cylindrical locksets
- Five stainless steel faceplates
- Field-selectable voltage
- 1,500 lbs. static strength
- Factory tested to 1,500,000 cycles
- UL listed

## Product Line:

Part Number	Description
OE-MRTSTRIKE <span>NEW</span>	<b>Mortise all-in-one Fire Strike:</b> Cylindrical and mortise lockset compatibility, fire rated, ANSI standard Grade 1 certification, 5 stainless steel faceplates, field selectable voltage, fail safe/fail secure operation
<b>Additional Access Control Products</b>	
OE-UNISTRIKE	<b>Universal Electric Strike:</b> Cylindrical and mortise lockset compatibility, low-profile and non-handed, ANSI faceplate, field selectable voltage, fail safe/fail secure operation
OE-RKSWTCH	<b>Surface Mount Rocker Switch:</b> Momentary (default) or maintained operation, SPDT configuration, snap-on cover, 2-3/8" W x 2-3/8" H x 5/8" D
OE-MAG600LB (600 lb.) OE-MAG1200LB (1200 lb.)	<b>Single Door Magnetic Lock:</b> 600 lbs. or 1200 lbs. holding force, compatible with all access control systems, brushed aluminum finish, field selectable voltage, on board MOV
OE-MAG600DS* (600 lb.) OE-MAG1200DS* (1200 lb.)	<b>Single Door Magnetic Lock with Bond Sensor:</b> 600 lbs. or 1200 lbs. holding force, includes bond sensor, door status switch and adjustable timer, compatible with all access control systems, brushed aluminum finish, field selectable voltage, on board MOV
OE-MAG600DB* (600 lb.) OE-MAG1200DB* (1200 lb.)	<b>Double Door Magnetic Lock:</b> 600 lbs. or 1200 lbs. holding force per door, for use on out-swinging doors, compatible with all access control systems, brushed aluminum finish, field selectable voltage, on board MOV
OE-LZB6 (600 lb.) OE-LZB12 (1200 lb.)	<b>L&amp;Z Brackets:</b> For use with 600 lb. or 1200 lb. magnetic locks on in-swinging single doors, brushed aluminum finish

\*Available in US/PR only

1.800.233.6261 | [adiglobal.com/adiexclusivebrands](http://adiglobal.com/adiexclusivebrands)

ADI  
a resideo company