

Data Sheet

RoamAlert® Tag ID Display

The Tag ID Display provides a local display of RoamAlert tag ID numbers at a door protected by a Door Controller.

The unit displays the most recent five tags detected by the Door Controller in a round-robin fashion on a bright and highly legible LED display. The facility can choose to display either the full six digits of the tag ID number, or only the last four. In the four-digit format, the Tag ID Display also shows the alarm condition (Loiter or Wander Alarm).

The display is automatically reset when the Door Controller is bypassed or when an alarm is acknowledged (either via the keypad or from a PC). It can also be configured to reset automatically after three minutes.

The Tag ID Display is compatible with all RoamAlert Door Controllers, and can be easily retro-fitted to existing Door Controllers.



Tag ID Display Specifications

Part Number	AR3DU01-000
Input Voltage	12 VDC @ 100mA
Wiegand Signal Input	32-bit message with 2 parity bits
Operating Temperature	32° to 131°F (0° to +55°C)
Storage Temperature	14° to 131°F (-10° to +55°C)
Humidity	90% Non-condensing
Cable Length	Up to 16.4 ft. (5m) using AWG 24 shielded cable
Mounting	Wall, low-voltage electrical box
Dimensions	4.5" x 2.75" x 1" (11.5 cm x 7 cm x 2.5 cm)

Product Highlights

- Bright and highly legible LED Display
- Selectable display format: 4 or 6 digits
- Shows Loiter or Wander Alarm condition with the tag ID number in 4-digit mode
- Wiegand interface to the Door Controller
- Simple operation: all options are selected during installation
- Easy to install or retro-fit



Phone: 800-824-2996
 North America: stanleyhealthcare@sbdinc.com
 Latin America: stanleyhealthcare-latam@sbdinc.com

Middle East: stanleyhealthcare-MEA@sbdinc.com
 Asia Pacific: stanleyhealthcare-asiapac@sbdinc.com
 Europe: shs-uk@sbdinc.com