



# APC NetShelter Rack PDU Advanced, Switched, 34.6kW, 3PH, 415V, 60A, 560P6, 42 Outlet

**Best Performance**

**APDU10450SW**

Call for More Information 800-800-4272

- APC NetShelter Rack PDU Advanced provide reliable power distribution to IT Equipment within server and/or networking racks. Switched outlets to turn outlets on or off remotely. PDU level power metering via remote access and local display for power visibility and notification of potential overload. 4-in-1 combination outlets which can be used as either C13, C19, C15, or C21 outlets provide unparalleled deployment flexibility. Maximum outlet density with 42 outlets in a 2.2" wide form factor. Outlets on the PDUs are color coded and/or labeled by breaker and input phase on 3 phase models to simplify deployment. Provides an alternating phase design whereby each of the 3 phases are organized into small outlet groups which alternate from top to bottom of the PDU to facilitate better power cord management and promote better load balancing. Power Sharing allows PDUs cascaded together via 2 ethernet ports enable an Network Management Card to continue functioning in the event of an AC power loss. No interruption in Network communication, sensors operation, and alarm traps. Live Swap Network Management Card (NMC) which can be replaced without powering down the PDU or connected devices to minimize downtime in the unlikely event of an NMC power event. Rated and approved to operate up to 60C (140F) at full load ensures reliability and availability even in today's high density deployments. Gigabit ethernet to enhance and standardize network connectivity across all assets in the data center. A second ethernet port (10/100) is available to allow cascading to other PDUs, connect to a 2nd private network, or provide network redundancy. 1% metering accuracy for the peace of mind to use NetShelter Rack PDU Advanced to bill based on power usage. In addition, the higher level of accuracy ensures the most precise measures for capacity planning and threshold alarm monitoring. Two environmental sensor ports allow for optional sensors (sold separately) to be connected. For data center deployments across multiple regions, these PDUs are both UL and CE rated providing one PDU that can be used globally to simplify and standardize deployment.

Output	
Nominal Output Voltage	240V
Overload Protection	Yes
Maximum Total Current Draw	48
Output Connections	(21) C13/C15 (21) C13/C15/C19/C21

Input	
Nominal Input Voltage	415V 3PH
Input frequency	50/60 Hz
Input Connections	IEC 60309 60 A 3P + N + PE

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Input	
Cord Length	5.91ft (1.8meters)
Acceptable Input Voltage	200 - 240, 346 - 415VAC
Load Capacity	34600VA
Maximum Input Current	60A
Regulatory Derated Input Current (North America)	48A

Physical	
Maximum Height	71.89inches (1826MM, 182.6CM)
Maximum Width	2.2inches (56MM, 5.6CM)
Maximum Depth	2.95inches (75MM, 7.5CM)
Net Weight	27.34lbs. (12.4KG)
Shipping weight	33.95lbs. (15.4KG)
Shipping Height	77.95inches (1980MM, 198.0CM)
Shipping Width	10.31inches (262MM, 26.2CM)
Shipping Depth	5.2inches (132MM, 13.2CM)
Color	Black

Environmental	
Operating Temperature	23 - 140 °F (-5 - 60 °C)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA C22.2 No 62368-1, FCC part 15 subpart B, UL 62368-1
Standard warranty	3 years repair or replace

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.