

# 10 Port Gigabit PoE Switch

8 Port PoE + 2 Port Uplink

0E-9P8POEGB2

**UltraTech**  
POWER PRODUCTS

## PRODUCT DESCRIPTION

The 10 Port Gigabit PoE Switch is fully integrated to support security monitoring, providing high-performance packet forwarding and gigabit Ethernet transfer rates. Adaptive ports use the appropriate bandwidth to ensure clear images and smooth transmission for any application, including high definition video recording or streaming.

## FEATURES

- **10 adaptive gigabit Ethernet ports:**
  - 8 x PoE ports (RJ45)
  - 1 x Uplink port (RJ45)
  - 1 x Uplink port (SFP)
- **Quick setup, with plug and play**
- **20 Gbps switching capacity**
- **120W PoE budget**
- **Port status LED indicator**
- **Power adapter included**
- **Energy efficient**
- **Standard: 802.3/802.3u/802.3ab/802.3af/at compliant**
- **Limited Lifetime Warranty**



## SPECIFICATIONS

<b>PART #</b>	<b>0E-9P8POEGB2</b>
<b>UPC</b>	840049309692
<b>INPUT POWER</b>	100-240 VAC
<b>TRANSMISSION DISTANCE</b>	328 ft. (100m)*
<b>MAC ADDRESS TABLE</b>	4K
<b>SWITCHING CAPACITY</b>	20 Gbps
<b>DIMENSIONS (L x W x H)</b>	7" x 4.2" x 1.1" (175 x 107 x 28mm)
<b>WEIGHT</b>	2.53 lbs. (1.15kg)

\*SFP transmission distance varies based on module used with device



# Commutateur PoE Gigabit à 10 ports



8 ports PoE + 2 port Uplink

0E-9P8POEGB2

## DESCRIPTION DU PRODUIT

Le commutateur PoE Gigabit à 10 ports permet une surveillance de la sécurité intégrée. Il offre une transmission de paquets à haute performance et une vitesse de transfert Gigabit rapide. Les ports actifs utilisent la bande passante appropriée pour des images limpides et une transmission efficace, peu importe l'application, y compris l'enregistrement et la diffusion vidéo haute définition.

## CARACTÉRISTIQUES

- **10 ports Ethernet Gigabit adaptatifs**
  - 8 ports PoE (RJ45)
  - 1 port Uplink (RJ45)
  - 1 port Uplink (SFP)
- **Configuration facile prête à l'emploi**
- **Capacité de commutation de 20 Go/s**
- **Puissance PoE totale de 120 W**
- **Indicateur à DEL d'état des ports**
- **Adaptateur inclus**
- **Efficacité énergétique**
- **Normes : Conformité 802.3/802.3u/802.3ab/802.3af/802.3at**
- **Garantie à vie limitée**



## SPÉCIFICATIONS

NO DE PIÈCE	0E-9P8POEGB2
CUP	840049309692
PUISSANCE D'ENTRÉE	100 à 240 VCA
DISTANCE DE TRANSMISSION	328 pi (100 m)*
TABLE D'ADRESSES MAC	4K
CAPACITÉ DE COMMUTATION	20 Go/s
DIMENSIONS (L x l x H)	7 x 4,2 x 1,1 po (175 x 107 x 28 mm)
POIDS	2,53 lb (1,15 kg)

\* La distance de transmission SFP varie en fonction du module utilisé avec l'appareil



# 10 Port Gigabit PoE Switch

## 8 Port PoE + 2 Port Uplink




### ADDITIONAL SPECIFICATIONS

<b>POWER</b>	Power Supply	External power supply	
	Voltage Range	54 VDC	
	PoE Power Budget	120W for PoE	
<b>ETHERNET</b>	Speed	Ports 1 to 9: 10/100/1000 Mbps Ports 10: 1.25 Gbps	
	Transmission Distance	Ports 1 to 9: 328 ft. (100m) Port 10: Transmission distance varies with type of SFP module used. (Module not included).	
<b>NETWORK SWITCH</b>	Ethernet Standard	IEEE 802.3/802.3u/802.3ab/802.3af/at	
	Switching Capacity	20 Gbps	
	Transfer Rate	14,880 pps for 10 Mbps 148,800 pps for 100 Mbps 1,488,000 pps for 1000 Mbps	
	MAC Address Table	4K MAC	
<b>LINK/ACT INDICATOR</b>	On	Green	Port connecting
	Blinks	-	Port receiving or transmitting data
	Off	-	Port is not successfully linked to device
<b>PoE</b>	On	Green	PD is connected
	Off	-	No PD is connected or power forwarding failed
	PoE PIN assignment	V+(RJ45 Pin 1,2), V-(RJ45 Pin 3, 6)	
<b>WORKING ENVIRONMENT</b>	Working Temperature	0 ~ 40°C (32 ~ 104°F)	
	Storage Temperature	-40 ~ 70°C (-40 ~ 158°F)	
	Humidity Non-Condensing	0 ~ 85%	
<b>MECHANICAL</b>	Dimensions (L x W x H)	7" x 4.2" x 1.1" (175 x 107 x 28mm)	
	Color	Black	

### PHYSICAL INTERFACE

Front



Back

