

# 350VA Battery Backup

## Compact UPS

0E-350V6

**UltraTech**  
POWER PRODUCTS

### PRODUCT DESCRIPTION

A compact UPS with standby topology, the UltraTech 0E-350V6 provides battery backup and surge protection for small electronics, computers, computer peripherals and audio equipment.

### FEATURES

- 6 Grounded Outlets, 3 with Battery Backup
- 2 Transformer Sized Outlets, 1 with Battery Backup
- HID Compliant USB Connectivity Port
- EMI and RFI Filtration
- Simulated Sine Wave Output
- Right Angle 45° Offset Plug



### SPECIFICATIONS

PART #	0E-350V6
UPC	811914022268
CAPACITY	350VA / 255W
OUTPUT	120 VAC +/- 5%
CORD LENGTH	5 ft. (1.5m)
OUTLET TYPES	6 x NEMA 5-15R
RUNTIME (HALF/FULL)	8 minutes / 2 minutes
DIMENSIONS	7.1 x 4.3 x 3.2 in. (180 x 109 x 81mm)
WEIGHT	3.5 lbs. (1.59kg)
WARRANTY	3-year
CONNECTED EQUIPMENT GUARANTEE	\$75,000

### TYPICAL APPLICATIONS

- Desktop Computers
- Workstations
- Home Theater Equipment
- Personal Electronics
- Home Networking
- Routers & Modems
- VoIP Phone Systems



# 350VA Battery Backup

Compact UPS

**UltraTech**  
POWER PRODUCTS



## ADDITIONAL SPECIFICATIONS

INPUT	Circuit Breaker	10A
	Cord Length	5 ft. (1.5m)
	Input Frequency Range	47 Hz-63 Hz
	Nominal Input Voltage	120 VAC
OUTPUT	On Battery Frequency	50/60 Hz +/- 1% (auto-sensing)
	On Battery Voltage	120 VAC +/- 5%
	On Battery Waveform	Simulated Sine Wave
	UPS Topology	Standby
	Overload Protection	Internal Circuitry Limiting, Circuit Breaker Protected
	Typical Transfer Time	4 ms
BATTERY	Battery Quantity	1, Replaceable by qualified technician
	Battery Size	12V
	Battery Type	Sealed Lead-Acid
	Typical Recharge Time	8 hours

# 350VA Battery Backup

Compact UPS



## ADDITIONAL SPECIFICATIONS (CONT.)

<b>SURGE PROTECTION AND FILTERING</b>	EMI / RFI Filtration	Yes
	Surge Suppression	810 J
<b>MANAGEMENT AND COMMUNICATIONS</b>	Audible Alarms	Battery Mode / Low Battery / Overload
	LCD	Multifunction LCD
	LED Indicators	Power On / Wiring Fault
<b>PHYSICAL SPECIFICATIONS</b>	Form Factor	Compact
	Material of Construction	Plastic
<b>WEIGHTS AND DIMENSIONS</b>	Width/Height/Depth (in)	7.1 x 4.3 x 3.2 in.
	Width/Height/Depth (cm)	18.03 x 10.92 x 8.13cm
	Width/Height/Depth (mm)	180 x 109 x 81mm
	Weight (lb) Weight (kg)	3.5 lbs. 1.59kg
<b>ENVIRONMENTAL</b>	Operating Relative Humidity	0 - 90% (non-condensing)
	Operating Temperature	32-104°F (0-40°C)
	Storage Temperature	5-113°F (-15-45°C)
<b>CERTIFICATIONS</b>	Environmental	RoHS Compliant
	Safety	UL1778 cUL FCC DOC Class B
<b>WARRANTY</b>	CEG Amount	\$75,000
	Product Warranty	3-Year Limited