

# 8-Outlet Basic PDU

## Network-Grade Power Distribution



0E-RCKMPDU8

### PRODUCT DESCRIPTION

A rackmount basic power distribution unit (PDU), the UltraTech 0E-RCKMPDU8 distributes power to eight receptacles from a single input with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, the 0E-RCKMPDU8 has a rugged, industrial-grade metal housing and can be mounted either horizontally or vertically.

### FEATURES

- 8 (Rear) Grounded Outlets
- 15-foot Power Cord
- Switch-Free Design
- Mount Vertically or Horizontally



### SPECIFICATIONS

PART #	0E-RCKMPDU8
UPC	840049303874
PHASE	Single
AMPS	15A (Derated to 12A)
VOLTS	100-125V
CORD LENGTH	15 ft. (4.6m)
OUTLET TYPES	8 × NEMA 5-15R
OUTLET LOCATION	8 Rear
DIMENSIONS	17.5 x 1.75 x 1.5 in. (445 x 44 x 38mm)
WEIGHT	3.4 lbs. (1.54kg)
WARRANTY	30 Months

### TYPICAL APPLICATIONS

- Workstations
- Corporate and Department Servers
- Network Devices
- Telecom Installations



# 8-Outlet Basic PDU

## Network-Grade Power Distribution



8 Outlets, Industrial-Grade Metal Housing

Vertical or Horizontal Rackmount

### ADDITIONAL SPECIFICATIONS

<b>INPUT</b>	Derated Input Current	12A
	Cord Length	15 ft. (4.6m)
	Input Frequency Range	50 Hz-60 Hz
	Maximum Input Current	15A
<b>OUTPUT</b>	Nominal Output Voltage	100-125 VAC
	Overload Protection	15A
<b>PHYSICAL SPECIFICATIONS</b>	Adjustable Mounting Brackets	2 sets: (2) Long L Brackets, (2) Short L Brackets
	Color	Black
	Cord Retention Tray	Yes
	External Site Ground Pin	Yes
	Form Factor	1U Rackmount / 0U Vertical Rackmount Undercounter Installation Supported
	Material of Construction	Metal
	Rack Height	1U
<b>WEIGHTS AND DIMENSIONS</b>	Width/Height/Depth (in)	17.5 x 1.75 x 1.5 in.
	Width/Height/Depth (cm)	44.45 x 4.45 x 3.81cm
	Width/Height/Depth (mm)	445 x 44 x 38mm
	Weight (lb)	3.4 lbs.
	Weight (kg)	1.54kg
<b>ENVIRONMENTAL</b>	Operating Relative Humidity	0 - 95% (non-condensing)
	Operating Temperature	32-95°F (0-35°C)
	Storage Temperature	5-113°F (-15-45°C)
<b>CERTIFICATIONS</b>	Environmental	RoHS Compliant
	Safety	UL1363 certified by ETL
<b>WARRANTY</b>	Product Warranty	30 Month Warranty