

# 2000VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS

0E-RCKMT2200

**UltraTech**  
POWER PRODUCTS

## PRODUCT DESCRIPTION

A rack/tower UPS with line interactive topology, the UltraTech 0E-RCKMT2200 provides battery backup and surge protection for servers, network devices and telecom installations without an active power factor correction (PFC) power supply. The 0E-RCKMT2200 uses Automatic Voltage Regulation (AVR) to correct minor power fluctuations without switching to battery power, which extends battery life, essential in locations with frequent power fluctuations.

## FEATURES

- Automatic Voltage Regulation (AVR)
- 2000VA / 1540W Capacity
- Sine Wave Output
- 8 Surge + Battery Backup Grounded Outlets
- LCD Display
- 2U Rack Mountable Chassis
- USB, Serial, EPO Communication
- Telephone and Ethernet Data Line Protection
- PowerPanel® Business Software for Remote Monitoring and Management (Free Download)



## SPECIFICATIONS

PART #	0E-RCKMT2200
UPC	840049301221
CAPACITY	2000VA / 1540W
OUTPUT	120 VAC +/- 5%
CORD LENGTH	10 ft. (3.0m)
OUTLET TYPES	2 x NEMA 5-20R 6 x NEMA 5-15R
RUNTIME (HALF/FULL)	15.5 minutes / 4.5 minutes
DIMENSIONS	17.01 x 3.5 x 15.32 in. (432 x 89 x 389mm)
WEIGHT	57.2 lbs. (25.95kg)
WARRANTY	3-year
CONNECTED EQUIPMENT GUARANTEE	\$300,000

## TYPICAL APPLICATIONS

- Workstations
- Corporate and Department Servers
- Network Devices
- Telecom Installations



# 2000VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS



8 Battery + Surge Protected Outlets  
2 x 20A + 6 x 15A

Telephone and Ethernet Data Line Protection  
USB + Serial + EPO Communication

## ADDITIONAL SPECIFICATIONS

INPUT	Circuit Breaker	15A
	Cord Length	10 ft. (3.0m)
	Input Frequency Range	57 Hz-63 Hz
	Nominal Input Voltage	120 VAC
OUTPUT	Automatic Voltage Regulation	Single Boost
	On Battery Frequency	60 Hz +/- 1%
	On Battery Waveform	Sine Wave
	UPS Topology	Line Interactive
	Overload Protection	Internal Circuitry Limiting
	Typical Transfer Time	4 ms
BATTERY	Battery Quantity	4 / User-Replaceable
	Battery Size	12V / 9Ah
	Replacement Battery Cartridge	RB1290X4H
	Typical Recharge Time	10 hours
SURGE PROTECTION AND FILTERING	EMI / RFI Filtration	Yes
	Phone / Network Protection RJ11 / RJ45	1-In / 1-Out (10/100)
	Surge Suppression	1470 J
MANAGEMENT AND COMMUNICATIONS	Audible Alarms	Battery Mode / Low Battery / Overload
	LCD	Multifunction LCD
	Software (Free Download)	PowerPanel® Business

# 2000VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS



## ADDITIONAL SPECIFICATIONS (CONT.)

<b>PHYSICAL SPECIFICATIONS</b>	Color	Black
	Form Factor	Rack / Tower
	Material of Construction	Metal
	Rack Height	2U
<b>WEIGHTS AND DIMENSIONS</b>	Width/Height/Depth (in) Width/Height/Depth (cm) Width/Height/Depth (mm)	17.01 x 3.5 x 15.32 in. 43.21 x 8.89 x 38.91cm 432 x 89 x 389mm
	Weight (lb) Weight (kg)	57.2 lbs. 25.95kg
<b>ENVIRONMENTAL</b>	Operating Relative Humidity	0 - 90% (non-condensing)
	Operating Temperature	32-104°F (0-40°C)
	Storage Temperature	5-113°F (-15-45°C)
<b>CERTIFICATIONS</b>	Environmental	RoHS Compliant
	Safety	UL1778 5th Edition cUL FCC DOC Class A
<b>WARRANTY</b>	CEG Amount	\$300,000
	Product Warranty	3-Year Limited