

12-Outlet Surge Protector

Network-Grade Surge Suppression

0E-RCKMTSURG

UltraTech
POWER PRODUCTS

PRODUCT DESCRIPTION

The professional-grade surge protector 0E-RCKMTSURG safeguards systems and networking equipment by absorbing spikes in energy caused by storms and electrical power surges. Designed for network environments, the 0E-RCKMTSURG also performs superbly for home office use. Industrial-grade metal housing keeps this unit performing flawlessly. Two sets of mounting brackets provide flexible installation options for horizontal, vertical and under-counter configurations.



FEATURES

- 3600J Surge Protection
- EMI/RFI Filtration
- 12 Grounded Outlets
- 15-foot Power Cord
- Mount Vertically or Horizontally

SPECIFICATIONS

PART #	0E-RCKMTSURG
UPC	840049301252
VOLTS	120V
CIRCUIT BREAKER	15A
CORD LENGTH	15 ft. (4.6m)
OUTLET TYPE	12 × NEMA 5-15R
OUTLET LOCATION	2 Front, 10 Rear
DIMENSIONS	17.5 x 1.75 x 2.25 in. (445 x 44 x 57mm)
WEIGHT	4.02 lbs. (1.82kg)
WARRANTY	Limited Lifetime
CONNECTED EQUIPMENT GUARANTEE	\$150,000

TYPICAL APPLICATIONS

- Workstations
- Corporate and Department Servers
- Network Devices
- Telecom Installations



12-Outlet Surge Protector

Network-Grade Surge Suppression

UltraTech
POWER PRODUCTS



12 Outlets, Industrial-Grade Metal Housing

Vertical or Horizontal
Rackmount

ADDITIONAL SPECIFICATIONS

INPUT	Cord Length	15 ft. (4.6m)
	Input Frequency Range	50 Hz-60 Hz
	Maximum Input Current	15A
OUTPUT	Nominal Output Voltage	120 VAC
	Overload Protection	15A
SURGE PROTECTION AND FILTERING	Attenuation	50 dB
	Clamping Voltage	400V (H-N, H-G, N-G)
	Maximum Surge Current	180,000 A
	Maximum Surge Current H-G	30000 A
	Maximum Surge Current H-N	120,000 A
	Maximum Surge Current N-G	30,000 A
	Maximum Surge Voltage	6000 V
	Response Time	1 Nanosecond
	Surge Suppression (Joules)	3600 J
MANAGEMENT AND COMMUNICATIONS	LED Indicators	Power On (green) Grounded (green)

12-Outlet Surge Protector

Network-Grade Surge Suppression



ADDITIONAL SPECIFICATIONS (CONT.)

PHYSICAL SPECIFICATIONS	Adjustable Mounting Brackets	2 sets: (2) Long L Brackets, (2) Short L Brackets
	Color	Black
	Cord Retention Tray	Yes
	External Site Ground Pin	Yes
	Form Factor	1U Rackmount / 0U Vertical Rackmount Undercounter Installation Supported
	Material of Construction	Metal
	Rack Height	1U
WEIGHTS AND DIMENSIONS	Width/Height/Depth (in) Width/Height/Depth (cm) Width/Height/Depth (mm)	17.5 x 1.75 x 2.25 in. 44.45 x 4.45 x 5.72cm 445 x 44 x 57mm
	Weight (lb) Weight (kg)	4.02 lbs. 1.82kg
ENVIRONMENTAL	Operating Relative Humidity	0 - 95% (non-condensing)
	Operating Temperature	32-95°F (0-35°C)
	Storage Temperature	5-113°F (-15-45°C)
CERTIFICATIONS	Environmental	RoHS Compliant
	Safety	UL1363 UL1449B
WARRANTY	CEG Amount	\$150,000
	Product Warranty	Limited Lifetime