COMELIT

DOOR ENTRY SYSTEMS

MINI AUDIO WITH HANDSET



2708W/A

SIMPLEBUS1 MINI DOOR ENTRY PHONE WITH HANDSET





Mini series door-entry phone with handset for Simplebus 1 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition.

AWARDS



COMELIT

DOOR ENTRY SYSTEMS

MINI AUDIO WITH HANDSET



2708W/A

	OOR ENTRY PHONE WITH HANDSET	
	GENERAL DATA	
Height (inch) (in)	7.48	
Width (inch) (in)	4.06	
Depth (inch) (in)	1.1	
Product color	White RAL9003	
Type of finishing materials	ABS	
Product weight (oz) (oz)	10.58	
Wall-mounted	Yes	
Desk base-mounted	Yes, with a dedicated accessory	
	AUDIO FEATURES	
Microphone	9.6 (ø) x 6.9mm, omnidirectional	
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W	
Technologies implemented	Full-Duplex	
EL	ECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus	
Supply voltage	22÷28VDC	
Maximum absorption (W)	0.6	
HARDWARE FEATURES		
Type of buttons	Mechanical	
Service buttons	Lock-release, Silent (Privacy)	
Clamps	L L CFP CFP	
Number of inputs (n°)	1	
SETTINGS		

23 ÷ 104

Operating temperature (°F)



DOOR ENTRY SYSTEMS

MINI AUDIO WITH HANDSET



2708W/A

SIMPLEBUS1 MINI DOOR ENTRY PHONE WITH HANDSET ENVIRONMENTAL AND COMPLIANCE FEATURES

ENVINOUMENTAL AND COM ENANCE I EATONES		
Operating humidity (RH max) (%)	25 ÷ 75	
Environmental class	I (B1)	
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)	

GENERAL FEATURES		
Door opener	Yes	
Absorption during call (mA)	25	
Absorption during communication (mA)	20	
Maximum current absorption (mA)	25	
Minimum current absorption (mA)	1	
Audio Simplebus 1	Yes	
CPS call	Yes	
Actuator control	Yes	
Outside door call input	Yes	
Silent mode (Privacy)	Yes	
Simplebus 1 audio system	Yes	
Output for call repetition	Yes	



DOOR ENTRY SYSTEMS

MINI AUDIO WITH HANDSET



2708W/A

SIMPLEBUS1 MINI DOOR ENTRY PHONE WITH HANDSET

ACCESSORIES



2711W MINI HS DOOR-ENTRY PHONE ADAPTER PLATE



2735 Ch. repeat. card+Mini HS door-entry phone button

Additional board for door-entry phones art. 2708W/A and 2738W/A for call repetition and for an additional button with voltage free contacts. Cable for connection to the main board and fixing screws provided.



2720W BRACKET FOR THROUGH-ROUTING OF EXTERNAL CABLES. MINI SERIES

Surface-mounted support for Mini door-entry phones with handset, allowing external routing of cables



2742W DESK BASE FOR MINI DOOR-ENTRY PHONE WITH HANDSET

Desk base for desktop conversion of MINI series door-entry phones. Complete with 1.5 m cable and connection coupling.