



PG9936H Heat Detector

Reliable, Early Fire Detection



Heat Only Detector

For areas such as kitchens, attics, and garages where the installation of a smoke detector is not recommended.



Temperature Warning

Temperatures exceeding 57°C (135°F) trigger the built-in 85 dB alarm, flash the LED light, and activate IQ Panel notifications and siren.



PowerG

Wireless security eliminates the need for wires, providing secure and reliable communication with an industry-leading range and encryption.



3-Year Battery Life

Adaptive transmission power maximizes battery life. (Typical Use)



Easy Installation

Quick wireless installation allows for flexible placement and easy maintenance.



Compatible Panels

Works with: IQ Panel 2+, IQ Panel 4, IQ4 Hub, IQ4 NS.

Specifications

Items	PG9936H
Dimensions	125 x 63mm (5 x 2.5in)
Battery Life	3 years (typical use)
Battery Type	3 AAA batteries (included)
Weight	243g (8.75oz)
Siren	Built-in 85db
Alarm Trigger Temperature	Exceed 57°C (135°F)
Sensing Technology	Thermistor-based sensing
Sensitivity Degradation	Audio and visual indicators notifying when cleaning or replacement of the detector is required
Installation Locations	Wall or Ceiling installation, with bracket
Operating Temperature	4.4°C to 37.8°C (40°F to 100°F)
Operating Environment	Indoors
Approvals	FCC, UL, CSFM (for PGx936)

For further information please refer to www.dsc.com