

STI Defibrillator Theft Stopper[®]



STI-6205

PRODUCT OVERVIEW

You've made a large investment in employee and consumer health and safety by purchasing an AED. Here is an effective way to help reduce the risk of theft.

HOW IT WORKS

The Defibrillator Theft Stopper incorporates a unique steel cable operated switch mechanism which sounds a powerful alarm when the cable is removed from the unit. Before use, the steel cable is permanently crimped around the handle of the AED. When the AED is removed from its normal position, the alarm will sound. The selectable 95 or 105 dB alarm can be very disturbing to potential thieves and will draw attention in a hurry. Alarm does not hinder access to the AED in any way and allows for proper use of the unit in a medical emergency. Reinserting the cable silences the alarm.

FEATURES

- Highly visible "stop sign" design discourages wrongful use of defibrillator.
- Sounds a powerful warning horn when activated; drawing attention in a hurry.
- Decibel level may be set to 95 dB for office settings or 105 dB for noisier environments.
- Deactivation cable provided for service to defibrillator by authorized personnel.
- Recommended operational range 32° to 120°F (0° to 49°C).
- Self-contained 9 VDC alkaline power source is provided.
- Compact design mounts easily next to defibrillator.
- Virtually indestructible polycarbonate housing.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

STI Defibrillator Theft Stopper®

Dimensions and Technical Information

MODEL AVAILABLE

STI-6205 Defibrillator Theft Stopper




NOTE: In moderate to high noise, a sound level check should be done (monthly) to verify audibility in all areas the unit is to alert. End user must verify the alarm and battery function every six months and replace battery annually or as required.

WARRANTY

Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

SPECIFICATIONS

Housing	1/8 in. Polycarbonate
Power Source	9 VDC Alkaline
Warning Horn at 1 foot	95 dB - Low 105 dB - High
Cable	1/8 in. galvanized steel 16 to 18 in. long
Dimensions	5.375 W x 5.375 H x 2 in. D 137 x 137 x 51mm
Standby Current	None
Alarm Current	40 mA at 95 dB 150 mA at 105 dB
Recommended Operating Temperature	32°F to 120°F (0°C to 49°C)



VIEW SHOWING JUMPER LOCATION FOR VOLUME SETTINGS

