



PRODUCT SPEC SHEET
R2-5MPFXTUR

5MP IP IR Fixed Turret

2560x1920 TRUE DAY/NIGHT



The R2-5MPFXTUR is a 5MP (2560 x1920) IP66 rated turret camera constructed with a 2.8mm lens and provides HD Image quality.

OPTIONAL SERVICES*

Integrate with Capture Cloud Service, powered by Eagle Eye*

Connect with Capture Remote Monitoring Service (R2-B12SUBK)*

**Require monthly/annual subscriptions*

FEATURES

- 2.8MM LENS
- IR DISTANCE: 30M/98FT
- SUPPORTS MICRO SD CARD, UP TO 256GB
- TRUE WDR
- ONVIF CONFORMANCE
- IP66
- POE/12VDC
- WARRANTY: 36 MONTHS
- PART #: R2-5MPFXTUR
- UPC: 840049305267
- DIMENSIONS: Ø4.65" x 3.7"
- WEIGHT: 1.21 LB



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

Caméra tourelle fixe IP IR 5 Mpx

JOUR/NUIT AUTHENTIQUE 2560 x 1920



Le modèle R2-5MPFXTUR est un camera tourelle 5 Mpx (2560 x 1920) certifiée IP66 dotée d'un objectif de 2.8 mm et offrant une qualité d'image HD.

SERVICES EN OPTION*

Intégrez-vous à Capture Cloud Service, optimisé par Eagle Eye.*

Connexion aux services de surveillance à distance de Capture (R2-B12SUBK)*

**Nécessite un abonnement mensuel ou annuel*

CARACTÉRISTIQUES

- OBJECTIF DE 2,8 MM
- DISTANCE (IR) : 30 M/98 PI
- PRISE EN CHARGE DES CARTES MICRO SD JUSQU'À 256 GO
- PLAGES DYNAMIQUES ÉTENDUES
- CONFORMITÉ ONVIF
- IP66
- POE/12 VCC
- GARANTIE : 36 MOIS
- NO DE PIÈCE : R2-5MPFXTUR
- UPC : 840049305267
- DIMENSIONS : Ø4.65 PO x 3.7 PO
- POIDS : 1,21 LB



POUR DE PLUS AMPLES RENSEIGNEMENTS, COMMUNIQUEZ AVEC UN REPRÉSENTANT ADI.

| CAMERA | |
|-------------------------|---|
| IMAGE SENSOR | 1/2.8" PROGRESSIVE SCAN CMOS |
| EFFECTIVE PIXELS | 2560 (H) × 1920 (V) |
| ELECTRONIC SHUTTER | AUTO/MANUAL, 1/5 - 1/20,000S |
| MIN. ILLUMINATION | COLOR: 0.05 LUX @ (F1.2, AGC ON) , B/W: 0 LUX @ (IR LED ON) |
| S/N RATIO | 55DB |
| DAY/NIGHT | AUTO(ICR) |
| WIDE DYNAMIC RANGE | TRUE WDR |
| IR RANGE | UP TO 30M (98 FT) |
| IR ON/OFF CONTROL | AUTO/MANUAL |
| PAN/TILT/ROTATION RANGE | PAN: 0° - 360°, TILT: 0° - 90°, ROTATION: ±60° |
| LENS | |
| LENS TYPE | FIXED FOCUS |
| IRIS | FIXED IRIS |
| FOCAL LENGTH | 2.8MM (4MM OPTIONAL) |
| F NUMBER | F2.0 |
| ANGLE OF VIEW | H: 93.4°, V: 69.1° |
| VIDEO | |
| MAX. RESOLUTION | 5MP (2592×1944) |
| STREAMING CAPABILITY | 3 STREAMS |
| STREAM/FRAME RATE | STREAM1: 2560×1920, 2592×1520, 1920×1080, 1280×720 @ 25/30FPS STREAM2: D1, VGA, CIF @ 25/30FPS STREAM3: VGA, CIF, QVGA @25/30FPS |
| BIT RATE CONTROL | CBR/VBR |
| BIT RATE | STREAM1: 200KBPS-12MBPS STREAM2: 100KBPS-6MBPS STREAM3: 100KBPS-3MBPS |
| IMAGE ENHANCEMENT | HLC / BLC / DEFOG / WDR |
| WHITE BALANCE | AUTO |
| GAIN CONTROL | AUTO/MANUAL |
| NOISE REDUCTION | 2D/3D DNR |
| AISLE MODE | SUPPORTED |
| SMART IR | SUPPORTED |
| MIRROR | SUPPORTED |
| REGION OF INTEREST | OFF/ON (8 ZONE, RECTANGLE) |
| MOTION DETECTION | SUPPORTED |
| PRIVACY MASKING | SUPPORTED |

| SMART FUNCTION | |
|-----------------------|--|
| SMART FUNCTION | SUPPORTS FACE, HUMAN, VEHICLE DETECTION |
| INTELLIGENT DETECTION | PERIMETER, SINGLE VIRTUAL FENCE, DOUBLE VIRTUAL, CONVERSE, PEOPLE COUNTING |
| AUDIO | |
| COMPRESSION | G.711, RAW_PCM |
| BIT RATE | 8KBPS, 16KBPS, 64KBPS |
| NETWORK | |
| PROTOCOLS | IPV4/IPV6, 802.1X, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPOE, SMTP, DNS, UPNP, FTP, ARP, SNMP, TLS/SSL |
| INTEROPERABILITY | ONVIF, SDK, CGI |
| STREAMING METHOD | UNICAST |
| MAX. USER ACCESS | 10 USERS |
| WEB VIEWER | <IE11, CHROME, FIREFOX, MICROSOFT EDGE |
| MANAGEMENT SOFTWARE | CAPTURE ADV |
| INTERFACE | |
| ETHERNET | 1 ETHERNET (10/100 BASE-T) RJ-45 CONNECTOR |
| AUDIO | 1CH INPUT, 1CH OUTPUT built-in Microphone |
| ALARM | 1CH INPUT, 1CH OUTPUT |
| RESET BUTTON | SUPPORTED |
| STORAGE | BUILT-IN MICRO SD SLOT, UP TO 256G |
| ELECTRICAL | |
| POWER SUPPLY | DC12V/POE (IEEE 802.3AF) |
| POWER CONSUMPTION | MAX 7.5 W |
| OPERATING TEMPERATURE | -40°C - 55°C (-40°F - 131°F) |
| OPERATING HUMIDITY | LESS THAN 90% RH |
| INGRESS PROTECTION | IP66 |
| CERTIFICATIONS | CE/FCC |
| CASING | METAL + PLASTIC |
| DIMENSIONS | φ118 x 94MM (4.65" x 3.7") |
| NET WEIGHT | 0.55 KG (1.04LB) |

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**