

850VA Battery Backup

Compact UPS

0E-850V8LCD

UltraTech
POWER PRODUCTS

PRODUCT DESCRIPTION

A compact UPS with standby topology, the UltraTech 0E-850V8LCD provides battery backup and surge protection for desktop computers, workstations, network devices, and home entertainment systems.

FEATURES

- 8 Grounded Outlets, 4 with Battery Backup
- 4 Transformer Sized Outlets, 2 with Battery Backup
- HID Compliant USB Connectivity Port
- EMI and RFI Filtration
- Simulated Sine Wave Output
- LCD Display
- PowerPanel® Personal Software for Remote Monitoring and Management



SPECIFICATIONS

PART #	0E-850V8LCD
UPC	840049307322
CAPACITY	850VA / 510W
OUTPUT	120 VAC +/- 10%
CORD LENGTH	5 ft. (1.5m)
OUTLET TYPES	12 x NEMA 5-15R
RUNTIME (HALF/FULL)	7.9 minutes / 2.3 minutes
DIMENSIONS	12.2 x 3.1 x 7 in. (310 x 79 x 178mm)
WEIGHT	7.70 lbs. (3.49kg)
WARRANTY	3-year
CONNECTED EQUIPMENT GUARANTEE	\$100,000

TYPICAL APPLICATIONS


- Desktop Computers
- Workstations
- Home Theater Equipment
- Personal Electronics
- Home Networking
- Routers & Modems
- VoIP Phone Systems



850VA Battery Backup

Compact UPS

UltraTech
POWER PRODUCTS



ADDITIONAL SPECIFICATIONS

INPUT	Circuit Breaker	15A
	Cord Length	5 ft. (1.5m)
	Input Frequency Range	47 Hz-63 Hz
	Nominal Input Voltage	120 VAC
OUTPUT	On Battery Frequency	50/60 Hz +/- 1% (auto-sensing)
	On Battery Voltage	120 VAC +/- 5%
	On Battery Waveform	Simulated Sine Wave
	UPS Topology	Standby
	Overload Protection	Internal Circuitry Limiting, Circuit Breaker Protected
	Typical Transfer Time	4 ms
BATTERY	Battery Quantity	1, Replaceable by qualified technician
	Battery Size	12V
	Battery Type	Sealed Lead-Acid
	Typical Recharge Time	8 hours

850VA Battery Backup

Compact UPS



ADDITIONAL SPECIFICATIONS (CONT.)

SURGE PROTECTION AND FILTERING	EMI / RFI Filtration	Yes
	Surge Suppression	526 J
MANAGEMENT AND COMMUNICATIONS	Audible Alarms	Battery Mode / Low Battery / Overload
	HID Compliant USB Port	Yes
	LCD	Multifunction LCD
	LED Indicators	Power On
	Management Cable	USB Cable
	Software (Free Download)	PowerPanel® Personal
	PHYSICAL SPECIFICATIONS	Form Factor
Material of Construction		Plastic
Keyhole Mounting Slots		Yes
WEIGHTS AND DIMENSIONS	Width/Height/Depth (in)	12.2 x 3.1 x 7 in.
	Width/Height/Depth (cm)	30.99 x 7.87 x 17.78cm
	Width/Height/Depth (mm)	310 x 79 x 178mm
ENVIRONMENTAL	Weight (lb)	7.70 lbs.
	Weight (kg)	3.49kg
	Operating Relative Humidity	0 - 90% (non-condensing)
ENVIRONMENTAL	Operating Temperature	32-104°F (0-40°C)
	Storage Temperature	5-113°F (-15-45°C)
	CERTIFICATIONS	Environmental
Safety		UL1778 FCC Part 15 Class B CSA C22.2 No. 107.3-05 FCC DOC Class B
WARRANTY	CEG Amount	\$100,000
	Product Warranty	3-Year Limited