

SKYSHIELD BASE

All-In-One Outdoor Surveillance Solution
Deployment for **Anywhere with Power**

SS-KG1-B2E

SkyShield Base Includes:

- 1x NEMA enclosure System and Accessory with Built-in Thermostat Heater, Fan and Strobe Lights
- Broad camera selection options
- 1x 5 Ports POE switch
- 1x 4 Ports 4G LTE Router
- 3Y SkyShield License include Core AI for Cameras in SkyShield*, the SkyShield Add-on Module License (Remote Power Control, Virtual Guard Dashboard) and Warranty



sales@turingvideo.com | 877.730.8222 | turing.ai

CAMERA OPTION(S)

SS-KG1-B2E



EVD5FT256-1Y & EVD5ZT256-1Y



EVC5FD256-1Y & EVC5ZD256-1Y



EVC5FB256-1Y & EVC5ZB256-1Y

Feature	EVD5FT256-1Y (Turret)	EVD5ZT256-1Y (Turret)	EVC5FD256-1Y (Dome)	EVC5ZD256-1Y (Dome)	EVC5FB256-1Y (Bullet)	EVC5ZB256-1Y (Bullet)
Resolution and Low Light Sensitivity : 5MP, 0.005 LUX @ F1.6						
Cloud VMS CORE AI-Ready						
Direct-to-Cloud with Onboard Storage						
3-click Easy Installation and NDAA Compliance						
Extended Warranty : Up to 10-year with CORE AI license						
Image Sensor Size	1/2.7	1/2.8	1/2.7	1/2.8	1/2.7	1/2.8
Lens Type	2.8 mm fixed	2.7-13.5mm zoom	2.8 mm fixed	2.7-13.5mm zoom	2.8 mm fixed	2.7-13.5mm zoom
Viewing Angles	H: 111°; V: 59°; D: 133°	H: 106~32°; V: 55~18°; D: 129~37°	H: 111°; V: 59°; D: 133°	H: 106~32°; V: 55~18°; D: 129~37°	H: 111°; V: 59°; D: 133°	H: 106~32°; V: 55~18°; D: 129~37°

SPECIFICATIONS

SS-KG1-B2E

GENERAL	
Dimensions (HxWxD)	23.8" x 19.1" x 10.4"(605 x 485 x 265mm)
Weight	40lbs(without camera)
Working Environment	-25°C~+ 55°C (-13°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Rating	IP55

POWER	
Power	AC110V Power consumption: ~64W(without camera)
Power Interface	Cable Conduit Connector

HEAT AND FAN	
Heat	Heater Capacity: 150W Heater turn on at 59°F(15°C)
Fan	MTBF: 10 years Fan turn on at 86°F(30°C)

NETWORK (CELLULAR)	
Standard and Band	4G (LTE-FDD): B2, B4, B5, B12, B13, B14, B66, B71 3G: B2, B4, B5
Antenna Interface	2 x SMA for LTE, 2 x RP-SMA for WiFi, 1 x SMA for GNSS
SIM Slot	2 x SIM slots (Mini SIM - 2FF), 1.8 V/3 V, external SIM holders, eSIM (Optional)
SIM switch	2 SIM cards, auto-switch cases: weak signal, data limit, SMS limit, roaming, no network, network denied, data connection fail, SIM idle protection
OpenVPN	Multiple clients and a server can run simultaneously, 27 encryption methods


MOUNT OPTIONS Pole Mount


3.9 into 11.8 in dia Stainless Steel Adjustable Clamp x4 (Included)



MOUNT OPTIONS Wall Mount

M8 x 80
(Not included in Product)





KEY FEATURES



Receive Instant Smart Alerts for Intruders/Trespassers/Person of Interest/Vehicle of Interest via SMS/Email/Push Notifications

Remote Live Stream Monitoring



- Remote Live Streaming up to 16 Cameras in HD
- Bookmark and Auto-Cycle Play for Live Monitoring



Share Live Camera Streams With First Responders



Find Events Fast with Smart Video Search and Archive/Share for Future Reference



View Live Footage From any Desktop / Mobile Device



Flexible Hybrid Storage Locally or on the Cloud