

Thermal Bullet IP Camera

400x300, 4 Lens Options



The R2-THRMLBLx is a thermal bullet camera with 4 lens options: 8mm, 15mm, 19mm and 35mm. The camera supports temperature measurement and intelligent analysis.

FEATURES

- UNCOOLED VOX MICRO BOLOMETER WITH 400x300 RESOLUTION AND ≤40MK THERMAL SENSITIVITY
- 8/15/19/35MM FIXED LENS MODELS
- TEMPERATURE MONITORING AND EXCEPTION ALARM
- TEMPERATURE DETECTION: -4°F TO 302°F (-20°C TO 150°C)
- TEMPERATURE MEASUREMENT RULE TYPES
- INTELLIGENT ANALYSIS: INTRUSION, LINE CROSSING, LOITERING, WRONG WAY, PEOPLE COUNTING, ENTER AREA, LEAVE AREA
- POE (12V DC)
- IP66 RATED
- WARRANTY: 36 MONTHS

- | ● PART #: | ● UPC: |
|--------------------------|--------------|
| R2-THRMLBL1 8MM LENS | 840049308442 |
| R2-THRMLBL2 15MM LENS | 840049308459 |
| R2-THRMLBL3 19MM LENS | 840049308466 |
| R2-THRMLBL4 35MM LENS | 840049308473 |
- DIMENSIONS: Ø4.33" x 15.28"
 - WEIGHT: 4.97 LB (WITH 15MM LENS)



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

THERMAL CAMERA

| | | | | |
|--|--|--------------------|--------------------|----------------|
| DETECTOR TYPE | UNCOOLED VOX MICRO BOLOMETER 400×300 | | | |
| RESOLUTION | SENSOR IS 400×300. IMAGE CAN BE SCALED UP TO 704×576 | | | |
| PIXEL PITCH | 17 UM | | | |
| SPECTRAL RANGE | 8-14MM | | | |
| THERMAL SENSITIVITY (NETD) | ≤ 40 MK | | | |
| LENS TYPE | FIXED | | | |
| FOCUS CONTROL | MANUAL FOCUS | | | |
| FOCAL LENGTH | 8MM | 15MM | 19MM | 35MM |
| F NO. | F1.0 | F1.0 | F1.0 | F1.0 |
| ANGLE OF VIEW | H:46° V:35.3° | H:25.5° V:19.2° | H:20.4° V:15.3° | H: 11° V:9° |
| DETECTION DISTANCE FIRE (1*1M) | 235M | 441M | 559M | 1029M |
| DETECTION DISTANCE MAN (1.8*0.5M) | 235M | 441M | 559M | 1029M |
| DETECTION DISTANCE VEHICLE (4*1.5M) | 722M | 1353M | 1714M | 3137M |
| RECOGNITION DISTANCE HUMAN (1.8*0.5M) | 59M | 110M | 152M | 257M |
| RECOGNITION DISTANCE VEHICLE (4*1.5M) | 180M | 338M | 467M | 789M |

VIDEO AND AUDIO

| | |
|---------------------------|--|
| MAIN STREAM | 704×576 @ 25/30FPS |
| SUB STREAM | CIF @ 25/30FPS |
| BIT RATE CONTROL | CBR/VBR |
| BIT RATE | MAIN STREAM: 100KBPS ~ 6MBPS SUB STREAM: 10KBPS ~ 1.5MBPS |
| REGION OF INTEREST | OFF / ON (8 ZONE, RECTANGLE) |
| SMART ENCODE | SUPPORTED |

| | |
|--------------------------|-------------------------------|
| AUDIO COMPRESSION | G.711: 8KBPS, RAW_PCM: 16KBPS |
|--------------------------|-------------------------------|

IMAGE

| | |
|-----------------------------|---|
| IMAGE SETTING | BRIGHTNESS, SHARPNESS, CONTRAST |
| MIRROR | SUPPORTED |
| PSEUDO-COLOR SETTING | WHITE-HOT/BLACK-HOT/RAINBOW/IRONBOW ETC. UP TO 17 MODES |
| DVE IMAGE ENHANCE | SUPPORTED |
| NOISE REDUCTION | 2D/3D DNR |
| PRIVACY MASKING | SUPPORTED |

SMART FUNCTIONS

| | |
|-----------------------------|---|
| SMART ALARM | MOTION DETECTION, DISK ALARM, I/O ALARM, IVS ALARM, TEMPERATURE DETECTION AND ALARM |
| AI MULTI-OBJECT | SUPPORTS HUMAN AND VEHICLE DETECTION |
| INTELLIGENT ANALYSIS | INTRUSION, SINGLE LINE CROSSING, DOUBLE LINE CROSSING, LOITERING, WRONG WAY, ENTER AREA, LEAVE AREA (THESE 7 FUNCTION SUPPORT ACCURATE DETECTION OF PEOPLE/VEHICLES), PEOPLE COUNTING |

TEMPERATURE DETECTION

| | |
|--------------------------------------|---|
| TEMPERATURE DETECTION | SUPPORTS 3 TEMPERATURE MESUREMENT RULE TYPES (SPOT, LINE, AREA) |
| TEMPERATURE ALARM | OVER TEMPERATURE ALARM, TEMPERATURE DIFFERENCE ALARM |
| ACCURACY | 32°C / 32% |
| RESPONSE TIME | ≤ 30MS |
| TEMPERATURE MEASUREMENT RANGE | -20°C ~ 150°C (-4°F ~ 302°F) |
| TEMPERATURE DISPLAY MODE | TEMPERATURE TARGET >5°C DISPLAY ABSOLUTE TEMPERATURE VALUE, TEMPERATURE TARGET ≤5°C DISPLAY RELATIVE TEMPERATURE VALUE (TEMPERATURE DIFFERENCE DEV = HIGHEST VALUE - AVERAGE) |

FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.

| NETWORK | |
|----------------------------|---|
| PROTOCOLS | IPV4/IPV6 ,HTTP,RTSP/RTP/RTCP, TCP/UDP, DHCP, DNS, PPPOE, SMTP, 802.1X |
| INTEROPERABILITY | ONVIF, CGI, SDK |
| MAX. USER ACCESS | 10 USERS |
| WEB VIEWER | <IE11, CHROME, FIREFOX, MICROSOFT EDGE |
| WEB LANGUAGE | ENGLISH, CHINESE, POLISH, ITALIAN, PORTUGUESE, SPANISH. RUSSIAN, FRENCH, CZECH, HUNGARIAN |
| INTERFACE | |
| NETWORK INTERFACE | 1 ETHERNET (10/100 BASE-T) RJ45 CONNECTOR |
| AUDIO INTERFACE | 1CH INPUT, 1CH OUTPUT |
| ALARM INTERFACE | 2CH INPUT, 2CH OUTPUT |
| RS485 | SUPPORTED |
| RESET BUTTON | SUPPORTED |
| SD CARD SLOT | SUPPORTED, UP TO 128GB |
| GENERAL | |
| POWER SUPPLY | DC12V/POE (IEEE 802.3AF) |
| POWER CONSUMPTION | MAX 5W |
| WORKING TEMPERATURE | -40°C - 60°C (-40°F - 140°F) |
| STORAGE CONDITIONS | 0- 90% RH |
| CERTIFICATIONS | CE/FCC |
| INGRESS PROTECTION | IP66 |
| CASING | METAL |
| DIMENSIONS | ø110 × 388MM (ø4.33 × 15.28 INCHES) |
| NET WEIGHT | 1.8KG (4.97 LB) WITH 15MM LENS |

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**