



SMT-3240

32" LED monitor



Key Features

- 32 inch UHD Monitor, support up to 3840×2160@60Hz
- Brightness 300 cd/m² (Typ) , Contrast 700:1 (Min) 1000:1 (Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 14ms(Typical)
- Video Input : HDMI, DP
- Frameless design with monitor stand
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3240

32" LED monitor



Specifications

Display	
Type	LED Monitor
Screen Size	31.5"
Max. Resolution	3840*2160 60Hz (UHD)
Brightness	300 cd/m ² (Typ)
Contrast Ratio	700:1 (Min) '1000:1 (Typ)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	1.07B Colors(Typ)
Response Time	14ms(Typical)
Panel Life	30,000 hours

Interface		
Video	Connectors	HDMI 2.0(1), DP1.2(1)
	Connector	HDMI
HDMI	Available Format	640 x 480@60Hz,800 x 600@56Hz/60Hz,1024 x 768@60Hz,1280 x 720@60Hz,1280x800@60Hz,1280x960@60Hz,1280x1024@60Hz, 1360x 768@60Hz,1440x900@60Hz,1680x1050@60Hz,1920x1080@60Hz,2560 x 1440@60Hz,3840 x 2160@60Hz,640 x 480P@60Hz,720x480P60Hz,1280 x 720P@60Hz,720x576P@50Hz, 1280x720P@50Hz,1920x 1080I@50/60Hz,1920x1080P@50/60Hz,720x480P@60Hz,3840x 2160P@30/50/60Hz,1440x480P@60Hz,1440x576P@50Hz,1440x 576P@50Hz,1440x480P@60Hz
	Connector	DP
DP	Available Format	640 x 480@60Hz,800 x 600@56Hz/60Hz,1024 x 768@60Hz,1280 x 720@60Hz,1280x800@60Hz,1280x960@60Hz,1280x1024@60Hz, 1360x 768@60Hz,1440x900@60Hz,1680x1050@60Hz,1920x1080@60Hz,2560 x 1440@60Hz,3840 x 2160@60Hz,640 x 480P@60Hz,720x480P60Hz,1280 x 720P@60Hz,720x576P@50Hz, 1280x720P@50Hz,1920x 1080I@50/60Hz,1920x1080P@50/60Hz,720x480P@60Hz,3840x 2160P@30/50/60Hz,1440x480P@60Hz,1440x576P@50Hz,1440x 576P@50Hz,1440x480P@60Hz
Audio	Connector	Audio Out
	Output Signal	Loop-through line level(PC only), Speakers : 6Ω 2W x 2

On Screen Display

Functions	VESA™ DPM Compatible
Language	Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	<55W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com

Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Mechanical	Dimensions with Stand (WxHxD)	714.6*485.7*200.9mm
	Dimensions without Stand (WxHxD)	714.6*445.6*53.7mm
	Weight	8.0kg(with stand), 6.5Kg(without stand)
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm