

# Eaton EMAU06-10

Catalog Number: EMAU06-10

Eaton Managed rack PDU, 2U, L6-30P input, 5.76 kW max, 200-240V, 24A, 10 ft cord, Single-phase, Outlets: (12) C13, (4) C19

## General specifications



Product Name	Catalog Number
Eaton Managed Rack PDU	EMAU06-10
UPC	Product Length/Depth
743172082695	19 in
Product Height	Product Width
5 in	3.4 in
Product Weight	Warranty
13.3 lb	3 year
Compliances	Certifications
Contact Manufacturer	UL Listed

## defaultTaxonomyAttributeLabel

### Type

ePDU

### Form factor

2U

### Outlet control

Yes

### Accessories

Yes

### Package contents

Yes

### Operating Temperature

0° to 60°C (32° to 140°F)

### Mounting direction

Horizontal

### Color

Black

### Input connection

L6-30P

### Cord length

10 ft

### Wattage

5.76 kW max

### Amperage Rating

24A

### Input voltage

200-240V

### Phase

Single-phase

### Frequency rating

50-60 Hz

### Outlets

(12) C13, (4) C19

### Series

Managed

## Resources

### Certification reports

Eaton ePDU certificate of volatility

Eaton RoHS Declaration of Conformity: ePDU G3

### Drawings

Eaton ePDU Managed EMAU06-10 technical drawing

Eaton Advanced Monitored and Managed ePDU visio stencil

### Manuals and user guides

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 replace and configure eNMC module

Eaton ePDU G3 operations manual

Eaton ePDU G3 instruction set - system objects

Eaton Double-wide G3 ePDU installation and connectivity quick start guide

### Specifications and datasheets

Eaton Specification Sheet - EMAU06-10



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)