120VAC Surge Protector

Protects Intrusion Alarm and Fire Panels

0E-SPROACHW



PRODUCT DESCRIPTION

The high performance 0E-SPROACHW is a Type 2 Surge Protection Device that protects sensitive electronic loads connected to service panels, intrusion alarm panels, fire panels and devices connected directly to it, via parallel installation on 120VAC branch circuits. LED indicators for AC input and active surge protection are included. The NEMA Type 1 sealed ABS plastic enclosure is weather and impact resistant.

FEATURES

- Surge Protection Device Type 2
- Service voltage: Single (2 wire + ground) 120VAC
- 15" lead wires
- Weather and impact resistant NEMA Type 1 enclosure
- LEDs for AC input and active surge protection
- UL1449, 4th Edition listed



PART#	0E-SPROACHW
UPC	811914024927
MCOV	130V
VPR	800V V-N 900V L-G 800V N-G
SURGE CURRENT RATING	18kVA
SCCR	10kA
NOM. DISCHARGE CURRENT	3kA RATING (IN)
OPERATING TEMPERATURE	-40°F to 185°F (-40°C to 60°C)
HUMIDITY RANGE	5-95% RH, non-condensing
DIMENSIONS (CASE ONLY) (L x W x H)	2.75" x 2.0" x 1.75" (70 x 51 x 44mm)
WEIGHT	9.2 oz. (261g)







