

6-Outlet Swivel Surge Protector with USB Charging

0E-SRGESWVL6

UltraTech
POWER PRODUCTS

PRODUCT DESCRIPTION

The 0E-SRGESWVL6 is ideal for home and office applications, providing vital surge protection for personal computers, phones/fax/modems, printers, stereos and other electronics. 0E-SRGESWVL6 features a convenient wall-tap design with six swivel outlets, as well as two USB ports for keeping tablets, smart phones and other rechargeable electronics ready to use.

FEATURES

- 6 Swivel Outlets, Surge Protected and Grounded
- 2 USB-A Charging Ports
- 1,200 Joules Surge Protection
- EMI/RFI Filtration
- Wall-Tap Plug
- Protected and Grounded LED Indicators



SPECIFICATIONS

PART #	0E-SRGESWVL6
UPC	840049304567
SURGE SUPPRESSION	1200J
VOLTS	125V
USB CHARGE PORTS	2 USB-A (2.4A shared)
OUTLET TYPES	6 × NEMA 5-15R
PLUG STYLE	Wall-Tap
DIMENSIONS	4.2 x 6.4 x 2.5 in. (107 x 163 x 64mm)
WEIGHT	0.65 lbs. (0.3kg)
WARRANTY	One-Year Limited
CONNECTED EQUIPMENT GUARANTEE	\$75,000

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Personal Computers



6-Outlet Swivel

Surge Protector with USB Charging



ADDITIONAL SPECIFICATIONS

INPUT	Plug Style	Wall-Tap
	Maximum Input Current	15A
OUTPUT	Outlet Type	6 x NEMA 5-15R
	USB Charge Ports	2 USB-A
	USB Charge Port Amperage	2.4A (Shared)
	USB Charge Port Voltage	5 VDC
SURGE PROTECTION AND FILTERING	Attenuation	32 dB
	Clamping Voltage	500V (H-N, H-G, N-G)
	EMI/RFI Filtration	150 KHz / 100 MHz
	Maximum Surge Current	60,000 A
	Maximum Surge Current H-G	15,000 A
	Maximum Surge Current H-N	30,000 A
	Maximum Surge Current N-G	15,000 A
	Maximum Surge Voltage	6000 V
	Response Time	<1 Nanosecond
Surge Suppression (Joules)	1200 J	

6-Outlet Swivel

Surge Protector with USB Charging



ADDITIONAL SPECIFICATIONS (CONT.)

PHYSICAL SPECIFICATIONS	Form Factor	Direct Wall-Tap Plug
	Material of Construction	Plastic
WEIGHTS AND DIMENSIONS	Width/Height/Depth (in)	4.2 x 6.4 x 2.5 in.
	Width/Height/Depth (cm)	10.67 x 16.26 x 6.35cm
	Width/Height/Depth (mm)	107 x 163 x 64mm
	Weight (lb) Weight (kg)	0.65 lbs. 0.3kg
CERTIFICATIONS	Environmental	RoHS Compliant
	Safety	UL1449 3rd Edition cUL FCC DOE VI
WARRANTY	CEG Amount	\$75,000
	Product Warranty	One-Year Limited