



Battery Powered Smoke & Carbon Monoxide Alarm

Model 900-CUDR

2-in-1 Detection

Alerts you to both smoke & carbon monoxide (CO) using a single unit.

Easy-Install Mounting Bracket

Included for simple, quick installation in 4 orientations.

Self-Testing

Smoke & CO alarm is equipped with components that are always checking to ensure the device is operating as expected.*

Photoelectric Smoke Sensor

May detect visible fire particles associated with slow smoldering fires sooner than an ionization sensor.



*Images are representative only.
Actual product may vary slightly.*

ALERTS USER TO REPLACE ALARM AFTER 10 YEARS OF OPERATION

Description

The Battery Powered Smoke & Carbon Monoxide Alarm (2-AA batteries included), is equipped with self-testing components that are always checking to make sure the alarm is on and working.* This smoke and CO combo alarm helps protect you and your family from 2 dangerous threats – fire and carbon monoxide – in one unit. What's more, the included mounting bracket makes installation quick and easy. Battery-powered smoke alarms provide reliable detection even during power outages, for extra peace of mind.

Leading authorities recommend that both ionization and photoelectric smoke alarms be installed to help ensure optimal detection of the various types of fires that can occur within the home. Ionization sensing alarms may detect invisible fire particles (associated with fast flaming fires) sooner than photoelectric alarms. Photoelectric sensing alarms may detect visible fire particles (associated with slow smoldering fires) sooner than ionization alarms.

Alarm Warnings – featuring multi-color LEDs

Fire: The red LED will flash in sync with the alarm pattern (3 long beeps). The alarm will repeat this pattern until the unit is reset or smoke is eliminated.

Carbon Monoxide: The red LED will flash in sync with the alarm pattern (4 quick beeps). This continues until the smoke & carbon monoxide alarm is reset or the CO is eliminated.

Low Battery: One chirp and amber LED flash per minute.

Alarm Memory: Alerts a user if smoke or CO has been detected in the last 24 hours. If smoke has been detected, the red LED blinks every 15 sec. If CO has been detected, the red LED blinks twice every 15 sec.

Features & Benefits

- **2-in-1 Detection** - Alerts you to both smoke & carbon monoxide (CO) using a single unit.
- **Easy-Install Mounting Bracket** - (Included) for simple, quick installation in 4 orientations.
- **Self-Testing** - Smoke & CO alarm is equipped with components that are always checking to ensure the device is operating as expected.*
- **Photoelectric Smoke Sensor** - May detect visible fire particles associated with slow smoldering fires sooner than an ionization sensor.
- **Electrochemical CO Sensor** - Accurate and reliable CO detection during the unit's life, remains stable during temperature and humidity changes and resists reactions to household gases that may cause false readings or reduce sensitivity.
- **One-Touch Button** - performs the following functions:
 - Activates the Hush™ feature to temporarily silence nuisance alarms.
 - Tests the unit's electronics and verifies proper operation.
 - Silences a low battery chirp for up to 24 hours at a time for a maximum of 7 days.
 - Silences the end of life chirps for 24 hours at a time for a maximum of 7 days.
 - Resets the device during a CO alarm (Unit will re-enter alarm within 6 minutes of reset if 70 ppm or more of CO is present).

*Self-testing is not a substitute for a manual push test of the alarm. Perform a button test once per week to verify proper alarm operation.



Industry experts recommend specific locations for smoke alarms, such as every level and sleeping area of the dwelling. They also recommend a CO alarm be installed on each level of the home – ideally on any level with fuel burning appliances and outside of sleeping areas. See User Guide for further information.

Architectural and Engineering Specifications

The combination smoke and carbon monoxide alarm shall be Kidde Model 900-CUDR or approved equal. It shall be powered by two AA batteries. The temperature operating range shall be between 40°F and 100°F (4.4°C and 37.8°C) and the humidity operating range shall be 10% - 95% relative humidity, non condensing.

The unit shall incorporate a photoelectric smoke sensor with nominal sensitivity of 1.74 +/- 0.78 %/ft OBS. The CO sensor shall be of an electrochemical design and shall meet the sensitivity requirements of Underwriters Laboratories UL 2034 Single and Multiple Station Carbon Monoxide Alarms. The unit shall qualify for UL-approved wording on the package: "World's Most Accurate Carbon Monoxide Alarm."***

The combination alarm can be installed on the surface of any wall or ceiling following the UL/NFPA/Manufacturer's recommended placement guidelines. The alarm shall include a test button that will electronically simulate the presence of smoke and CO and cause the unit to go into both modes of alarm. This sequence tests the unit's electronics to ensure proper operation. The CO sensor will not alarm to levels of CO below 30 ppm and will alarm in the following time range when exposed to the corresponding levels of CO.

70 ppm CO Concentration: 60 – 240 minutes
150 ppm CO Concentration: 10 – 50 minutes
400 ppm CO Concentration: 4 – 15 minutes

The combination alarm shall warn of danger using a piezoelectric horn that is rated at 85 decibels at 10 feet. For a CO incident, the horn will sound in the repetitive manner – four (4) fast beeps, a short pause, four (4) fast beeps. After four minutes the alarm pattern will sound once every minute until the unit is reset, or the CO eliminated. In a Smoke incident, the horn will sound in the repetitive manner – three (3) beeps, a pause, three (3) beeps. The unit shall incorporate four (4) LEDs. A green LED will flash every 60 seconds when in standby condition. An amber LED will indicate fault conditions. A red LED will flash once or twice every 15 seconds to indicate smoke or CO alarm memory,

***Claim approved by UL, based on manufacturer's reported testing.

and will flash in unison with the sounder pattern during alarm. The unit shall include the Hush™ feature that silences a smoke alarm for approximately 8-10 minutes if a nuisance alarm condition occurs. The red LED on the alarm will flash every 2 seconds while in Hush™ and will automatically reset itself.

The unit shall also indicate a low battery warning utilizing a brief alarm chirp. The unit shall at a minimum meet the requirements of UL 2034, UL 217, NFPA 72, NFPA 101 (One and two family dwellings), Federal Housing Authority (FHA), Housing and Urban Development (HUD). It shall also include a 10-year manufacturer's limited warranty.

▲ WARNING: *This product is intended for use in indoor residential locations. It is not designed to measure compliance with Occupational Safety and Health Administration (OSHA) commercial or industrial standards. This device is designed to help protect individuals from acute effects of Carbon Monoxide exposure. It will not fully safeguard individuals with specific medical conditions. If in doubt, consult a medical practitioner. Individuals with medical problems may consider using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm.*

Technical Specifications

Model:	900-CUDR
Power Source:	2 AA batteries
Smoke Sensor:	Photoelectric
CO Sensor:	Electrochemical
Audio Alarm:	85dB at 10ft
Temperature Range:	40°F (4.4°C) to 100°F (37.8°C)
Humidity Range:	10%-95% relative humidity, non-condensing
Size:	4.95" in diameter x 1.93" depth
Weight:	0.530 lb
Interconnects:	No
Warranty:	10 year limited (batteries excluded)
Replacement batteries:	Energizer E91, Gold Peak 15A, Golden Power GLR6A. Replacement batteries are available where you purchased this alarm. <i>Note: Do not use lithium batteries in this unit.</i>

Ordering Information

Ordering Number	UPC	GTIN	Pack Config	Pack Qty	Case Dimensions (w x d x h inches)	Case Weight (lbs)	Cartons/Pallet
21032243	047871322435	10047871322432	Box	Tray/Lid (4 Units)	10.34 x 6.26 x 6	4.586	150
21032240	047871322404	N/A	Contractor Box	Bulk (6 units)	14.18 x 5.44 x 5.5	4.350	126
21032249	047871322497	10047871322494	Box	Tray/Lid (3 Units)	8.08 x 6.26 x 6.01	3.585	198



1016 Corporate Park Drive, Mebane, NC 27302
 1-800-880-6788 www.Kidde.com

A Carrier Company
 ©2022 Carrier. All Rights Reserved.
 All trademarks and service marks referred herein are property of their respective owners.

