

# 58160D Wireless Outdoor Contact/Transmitter

## Frequently Asked Questions



<b>Since this is an outdoor product, what are the temperature and humidity ranges?</b>	Temp -40° F to 150° F 100% RH (-40° C to 66° C)
<b>What type of outdoor rating does the product have?</b>	The weather-proof and water-resistant 58160D has passed NEMA 4X water protection. NEMA 4X Rating: Intended for indoor or outdoor use primarily to provide a degree of protection against corrosion, windblown dust and rain, splashing water, hose directed water and to be undamaged by the formation of ice on the enclosure.
<b>What is the wireless range of the product?</b>	Range is dependent upon of the type of construction and number of walls that the signal must pass through. We anticipate over 200 foot range in a typical installation. If additional range is needed, a repeater (5800RP) can be added.
<b>What is the gap of the product?</b>	1.75" on wood, vinyl and non-metallic surfaces and 1.25" on steel.
<b>What is the anticipated battery life?</b>	Battery life is based upon the number of transmissions per day. On a typical installation we anticipate approximately five years with lithium batteries.
<b>Is the battery replaceable?</b>	Yes, the device will indicate when it has a low battery condition. Replace with two Energizer® E2 AA lithium batteries.
<b>Do outside weather conditions affect range?</b>	No.
<b>Can the device be painted?</b>	Yes, however we recommend using specific paint designed for plastic surfaces. Krylon® "Fusion for Plastic", Rust-Oleum® "Plastic" or Dupli-Color® "Vinyl and Fabric Coating".
<b>Can the device be mounted on steel?</b>	Yes. In the case of a metal shed, the device should be mounted on the outside of the shed to prevent loss of range.